

1 Identification

Product identifier

Product name: Ethylenediamine

Stock number: A12132

CAS Number:

107-15-3

EC number:

203-468-6

Index number:

612-006-00-6

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Alfa Aesar

Thermo Fisher Scientific Chemicals, Inc.

30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660

Fax: 800-322-4757

Email: tech@alfa.com

www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency telephone number:

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

2 Hazard(s) identification

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)

 GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.

 GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

 GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

 GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Hazards not otherwise classified No information known.

Label elements

GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)

Hazard pictograms

   
GHS02 GHS05 GHS07 GHS08

Signal word Danger

Hazard statements

H226 Flammable liquid and vapor.

H302+H312 Harmful if swallowed or in contact with skin.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P260 Do not breathe dusts or mists.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

B3 - Combustible liquid

D1B - Toxic material causing immediate and serious toxic effects

D2A - Very toxic material causing other toxic effects

E - Corrosive material



Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH 3 Health (acute effects) = 3

FIRE 3 Flammability = 3

REACTIVITY 1 Physical Hazard = 1

Product name: *Ethylenediamine*

Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

(Contd. of page 1)

3 Composition/information on ingredients
Chemical characterization: Substances
CAS# Description:
107-15-3 Ethylenediamine
Concentration: ≤100%
Identification number(s):
EC number: 203-468-6
Index number: 612-006-00-6

4 First-aid measures
Description of first aid measures
General information Immediately remove any clothing soiled by the product.
After inhalation
Supply fresh air. If required, provide artificial respiration. Keep patient warm.
Seek immediate medical advice.
After skin contact
Immediately wash with water and soap and rinse thoroughly.
Seek immediate medical advice.
After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing Seek medical treatment.
Information for doctor
Most important symptoms and effects, both acute and delayed
Causes severe skin burns.
Harmful if swallowed.
Harmful in contact with skin.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures
Extinguishing media
Suitable extinguishing agents Carbon dioxide, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Special hazards arising from the substance or mixture
If this product is involved in a fire, the following can be released:
Carbon monoxide and carbon dioxide
Nitrogen oxides (NOx)
Advice for firefighters
Protective equipment:
Wear self-contained respirator.
Wear fully protective impervious suit.

6 Accidental release measures
Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Environmental precautions: Do not allow product to reach sewage system or any water course.
Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose of contaminated material as waste according to section 13.
Ensure adequate ventilation.
Prevention of secondary hazards: Keep away from ignition sources.
Reference to other sections
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
Protective Action Criteria for Chemicals
PAC-1: 0.88 ppm
PAC-2: 9.7 ppm
PAC-3: 20 ppm

7 Handling and storage
Handling
Precautions for safe handling
Handle under dry protective gas.
Keep container tightly sealed.
Store in cool, dry place in tightly closed containers.
Ensure good ventilation at the workplace.
Information about protection against explosions and fires:
Protect against electrostatic charges.
Fumes can combine with air to form an explosive mixture.
Keep ignition sources away.
Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility:
Store away from air.
Do not store together with acids.
Store away from oxidizing agents.
Further information about storage conditions:
Store under dry inert gas.
This product is air sensitive.
Keep container tightly sealed.

(Contd. on page 3)
USA

Product name: **Ethylenediamine**

Store in cool, dry conditions in well sealed containers.
Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems:
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring at the workplace:

107-15-3 Ethylenediamine (100.0%)	
PEL (USA)	Long-term value: 25 mg/m³, 10 ppm
REL (USA)	Long-term value: 25 mg/m³, 10 ppm
TLV (USA)	Long-term value: 25 mg/m³, 10 ppm
EL (Canada)	Long-term value: 10 ppm
EV (Canada)	Long-term value: 25 mg/m³, 10 ppm

Additional information: No data

Exposure controls

Personal protective equipment

General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Do not inhale dust / smoke / mist.

Avoid contact with the eyes and skin.

Maintain an ergonomically appropriate working environment.

Breathing equipment: Use suitable respirator when high concentrations are present.

Recommended filter device for short term use:

Use a respirator with multi-purpose combination (US) or type ABEK (EN 14387) as a backup to engineering controls. Risk assessment should be performed to determine if air-purifying respirators are appropriate. Only use equipment tested and approved under appropriate government standards such as NIOSH (USA) or CEN (EU).

Protection of hands:

Impervious gloves

Check protective gloves prior to each use for their proper condition.

The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Material of gloves Butyl rubber, BR

Penetration time of glove material (in minutes) 480

Glove thickness: 0.3 mm

Eye protection:

Tightly sealed goggles

Full face protection

Safety glasses with side shields / NIOSH (US) or EN 166(EU)

Body protection: Protective work clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form: Liquid

Odor: Ammonia-like

Odor threshold: Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range: 8-11 °C (46-52 °F)

Boiling point/Boiling range: 117 °C (243 °F)

Sublimation temperature / start: Not determined

Flash point: 38 °C (100 °F)

Flammability (solid, gaseous) Not determined.

Ignition temperature: 385 °C (725 °F)

Decomposition temperature: Not determined

Auto igniting: Not determined.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures is possible.

Explosion limits:

Lower: 2.7 Vol %

Upper: 16.6 Vol %

Vapor pressure at 20 °C (68 °F): 12 hPa (9 mm Hg)

Density at 20 °C (68 °F): 0.899 g/cm³ (7.502 lbs/gal)

Relative density Not determined.

Vapor density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with

Water: Fully miscible

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

dynamic at 25 °C (77 °F): 1.54 mPas

kinematic: Not determined.

Other information No further relevant information available.

10 Stability and reactivity

Reactivity No information known.

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions Reacts with strong oxidizing agents

Product name: *Ethylenediamine*

Conditions to avoid No further relevant information available.
Incompatible materials:
Acids
Air
Oxidizing agents
Hazardous decomposition products:
Carbon monoxide and carbon dioxide
Nitrogen oxides

(Contd. of page 3)

11 Toxicological information

Information on toxicological effects
Acute toxicity:
Harmful in contact with skin.
Harmful if swallowed.
Danger through skin absorption.
Swallowing will lead to a strong corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.
The Registry of Toxic Effects of Chemical Substances (RTECS) contains acute toxicity data for this substance.
LD/LC50 values that are relevant for classification:
Oral LD50 1200 mg/kg (rat)
Dermal LD50 656 mg/kg (rabbit)
Skin irritation or corrosion: Causes severe skin burns.
Eye irritation or corrosion: Causes serious eye damage.
Sensitization:
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Germ cell mutagenicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains mutation data for this substance.
Carcinogenicity:
EPA-D: Not classifiable as to human carcinogenicity: inadequate human and animal evidence of carcinogenicity or no data are available.
ACGIH A4: Not classifiable as a human carcinogen: Inadequate data on which to classify the agent in terms of its carcinogenicity in humans and/or animals.
Reproductive toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains reproductive data for this substance.
Specific target organ system toxicity - repeated exposure: No effects known.
Specific target organ system toxicity - single exposure: No effects known.
Aspiration hazard: No effects known.
Subacute to chronic toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains multiple dose toxicity data for this substance.
Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

12 Ecological information

Toxicity
Aquatic toxicity: No further relevant information available.
Persistence and degradability No further relevant information available.
Bioaccumulative potential No further relevant information available.
Mobility in soil No further relevant information available.
Additional ecological information:
General notes:
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Avoid transfer into the environment.
Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.
Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods
Recommendation Consult state, local or national regulations to ensure proper disposal.
Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.
Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number DOT, IMDG, IATA	UN1604
UN proper shipping name DOT ADR IMDG, IATA	Ethylenediamine 1604 Ethylenediamine ETHYLENEDIAMINE
Transport hazard class(es) DOT 	
Class Label ADR 	8 Corrosive substances 8, 3
Class	8 (CF1) Corrosive substances

(Contd. on page 5)
USA

Product name: **Ethylenediamine**

(Contd. of page 4)

Label	8+3
IMDG	
	
Class	8 Corrosive substances
Label IATA	8/3
	
Class	8 Corrosive substances
Label	8 (3)
Packing group	
DOT, ADR, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Corrosive substances
EMS Number:	F-E, S-C
Segregation groups	Alkalis
Stowage Category	A
Stowage Code	SW2 Clear of living quarters.
Segregation Code	SG35 Stow "separated from" acids.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L 5000 lbs, 2270 kg
Hazardous substance:	No
Marine Pollutant (DOT):	No
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1604 ETHYLENEDIAMINE, 8 (3), II

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)
Hazard pictograms



GHS02 GHS05 GHS07 GHS08

Signal word Danger

Hazard statements

H226 Flammable liquid and vapor.
H302+H312 Harmful if swallowed or in contact with skin.
H314 Causes severe skin burns and eye damage.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P260 Do not breathe dusts or mists.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.
All components of this product are listed on the Canadian Domestic Substances List (DSL).

SARA Section 313 (specific toxic chemical listings)

107-15-3 Ethylenediamine

California Proposition 65

Prop 65 - Chemicals known to cause cancer Substance is not listed.

Prop 65 - Developmental toxicity Substance is not listed.

Prop 65 - Developmental toxicity, female Substance is not listed.

Prop 65 - Developmental toxicity, male Substance is not listed.

Information about limitation of use: For use only by technically qualified individuals.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Global Marketing Department

(Contd. on page 6)
USA

Product name: *Ethylenediamine*

Date of preparation/Revision: *Print date, revision date and version number are in the header of each page.*

(Contd. of page 5)

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
ACGIH: American Conference of Governmental Industrial Hygienists (USA)
OSHA: Occupational Safety and Health Administration (USA)
NTP: National Toxicology Program (USA)
IARC: International Agency for Research on Cancer
EPA: Environmental Protection Agency (USA)
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1