

1 Identification

Product identifier

Product name: Lithium sulfide

Stock number: 12839

CAS Number:

12136-58-2

EC number:

235-228-1

Relevant identified uses of the substance or mixture and uses advised against.

Identified use: SU24 Scientific research and development

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Alfa Aesar

Thermo Fisher Scientific Chemicals, Inc.

30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660

Fax: 800-322-4757

Email: tech@alfa.com

www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency telephone number:

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

2 Hazard(s) identification

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)



GHS02 Flame

Flam. Sol. 1 H228 Flammable solid.

Water-react. 2 H261 In contact with water releases flammable gas.



GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

Hazards not otherwise classified No information known.

Label elements

GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)

Hazard pictograms



GHS02 GHS05 GHS06

Signal word

Danger

Hazard statements

H228 Flammable solid.

H261 In contact with water releases flammable gas.

H301 Toxic if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Precautionary statements

P223 Do not allow contact with water.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

B6 - Reactive flammable material

D1B - Toxic material causing immediate and serious toxic effects

D2B - Toxic material causing other toxic effects



Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH 3 Health (acute effects) = 3

FIRE 2 Flammability = 2

REACTIVITY 2 Physical Hazard = 2

Product name: *Lithium sulfide*

Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

(Contd. of page 1)

3 Composition/information on ingredients

Chemical characterization: Substances
CAS# Description:
12136-58-2 Lithium sulfide
Concentration: ≤100%
Identification number(s):
EC number: 235-228-1

4 First-aid measures

Description of first aid measures
After inhalation
Supply fresh air. If required, provide artificial respiration. Keep patient warm.
Seek immediate medical advice.
After skin contact
Immediately wash with water and soap and rinse thoroughly.
Seek immediate medical advice.
After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing Seek medical treatment.
Information for doctor
Most important symptoms and effects, both acute and delayed
Causes skin irritation.
Toxic if swallowed.
Causes serious eye damage.
Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media
Suitable extinguishing agents In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
For safety reasons unsuitable extinguishing agents Water
Special hazards arising from the substance or mixture
Reacts violently with water
If this product is involved in a fire, the following can be released:
Sulfur oxides (SOx)
Lithium oxide
Hydrogen sulfide
Advice for firefighters
Protective equipment:
Wear self-contained respirator.
Wear fully protective impervious suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Environmental precautions: Do not allow material to be released to the environment without proper governmental permits.
Methods and material for containment and cleaning up:
Keep away from ignition sources.
Dispose of contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Prevention of secondary hazards: Keep away from ignition sources.
Reference to other sections
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
Protective Action Criteria for Chemicals
PAC-1: Substance is not listed.
PAC-2: Substance is not listed.
PAC-3: Substance is not listed.

7 Handling and storage

Handling
Precautions for safe handling
Handle under dry protective gas.
Keep container tightly sealed.
Store in cool, dry place in tightly closed containers.
Ensure good ventilation at the workplace.
Information about protection against explosions and fires: Protect against electrostatic charges.
Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and receptacles: Store in a cool location.
Information about storage in one common storage facility:
Do not store together with acids.
Store away from water/moisture.
Further information about storage conditions:
Store under dry inert gas.
This product is moisture sensitive.
Protect from humidity and water.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.

(Contd. on page 3)
USA

Product name: *Lithium sulfide*

Specific end use(s) No further relevant information available. (Contd. of page 2)

8 Exposure controls/personal protection

Additional information about design of technical systems:
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters
Components with limit values that require monitoring at the workplace:
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: No data

Exposure controls
Personal protective equipment
General protective and hygienic measures
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Remove all soiled and contaminated clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Maintain an ergonomically appropriate working environment.

Breathing equipment: Use suitable respirator when high concentrations are present.

Recommended filter device for short term use:
Use a respirator with type P100 (USA) or P3 (EN 143) cartridges as a backup to engineering controls. Risk assessment should be performed to determine if air-purifying respirators are appropriate. Only use equipment tested and approved under appropriate government standards.

Protection of hands:
Impervious gloves
Check protective gloves prior to each use for their proper condition.
The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Material of gloves Nitrile rubber, NBR
Penetration time of glove material (in minutes) 480

Glove thickness: 0.11 mm

Eye protection:
Tightly sealed goggles
Full face protection
Safety glasses with side shields / NIOSH (US) or EN 166(EU)

Body protection: Protective work clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties
General Information
Appearance:
Form: Powder
Odor: Like rotten eggs
Odor threshold: Not determined.

pH-value: Not applicable.

Change in condition
Melting point/Melting range: 900-975 °C (1652-1787 °F)
Boiling point/Boiling range: Not determined
Sublimation temperature / start: Not determined
Flammability (solid, gaseous) Highly flammable.
Ignition temperature: Not determined
Decomposition temperature: Not determined
Auto igniting: Not determined.

Danger of explosion: Not determined.

Explosion limits:
Lower: Not determined
Upper: Not determined

Vapor pressure: Not applicable.
Density at 20 °C (68 °F): 1.66 g/cm³ (13.853 lbs/gal)
Relative density Not determined.
Vapor density Not applicable.
Evaporation rate Not applicable.

Solubility in / Miscibility with
Water: Reacts violently
Partition coefficient (n-octanol/water): Not determined.

Viscosity:
dynamic: Not applicable.
kinematic: Not applicable.

Other information No further relevant information available.

10 Stability and reactivity

Reactivity
Reacts violently with water.
Contact with acids liberates toxic gas.

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions
Reacts violently with water
Contact with acids liberates toxic gas.

Conditions to avoid No further relevant information available.

Incompatible materials:
Acids
Water/moisture

Hazardous decomposition products:
Lithium oxide
Sulfur oxides (SOx)
Hydrogen sulfide

Product name: **Lithium sulfide**

(Contd. of page 3)

11 Toxicological information

Information on toxicological effects

Acute toxicity: Toxic if swallowed.

LD/LC50 values that are relevant for classification:

Oral	LD50	1200 mg/kg (mouse)
		240 mg/kg (rat)

Skin irritation or corrosion: Causes skin irritation.

Eye irritation or corrosion: Causes serious eye damage.

Sensitization: No sensitizing effects known.

Germ cell mutagenicity: No effects known.

Carcinogenicity: No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

Reproductive toxicity: No effects known.

Specific target organ system toxicity - repeated exposure: No effects known.

Specific target organ system toxicity - single exposure: May cause respiratory irritation.

Aspiration hazard: No effects known.

Subacute to chronic toxicity: No effects known.

Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability: No further relevant information available.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Additional ecological information:

General notes:

Do not allow material to be released to the environment without proper governmental permits.

Do not allow undiluted product or large quantities to reach ground water, water course or sewage system.

Avoid transfer into the environment.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects: No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation: Consult state, local or national regulations to ensure proper disposal.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number

DOT, IMDG, IATA

UN3134

UN proper shipping name

DOT

ADR

IMDG, IATA



Water-reactive solid, toxic, n.o.s. (Lithium sulfide)

3134 Water-reactive solid, toxic, n.o.s. (Lithium sulfide)

WATER-REACTIVE SOLID, TOXIC, N.O.S. (Lithium sulfide)

Transport hazard class(es)

DOT





Class

Label

ADR

4.3 Substances which, in contact with water, emit flammable gases

4.3, 6.1





Class

Label

IMDG

4.3 (WT2) Substances which, in contact with water, emit flammable gases

4.3+6.1





Class

Label

IATA

4.3 Substances which, in contact with water, emit flammable gases

4.3/6.1



Class

Label

4.3 Substances which, in contact with water, emit flammable gases

4.3 (6.1)

Packing group

DOT, ADR, IMDG, IATA

II

Environmental hazards:

Not applicable.

Special precautions for user

EMS Number:

Stowage Category

Warning: Substances which, in contact with water, emit flammable gases

F-G,S-N

E




(Contd. on page 5)
USA

Product name: Lithium sulfide

(Contd. of page 4)

Stowage Code Handling Code Segregation Code	SW3 Shall be transported under temperature control. H1 Keep as dry as reasonably practicable SG26 In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.	
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 15 kg On cargo aircraft only: 50 kg No
Marine Pollutant (DOT):	No
IMDG Limited quantities (LQ) Excepted quantities (EQ)	500 g Code: E2 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 500 g
UN "Model Regulation":	UN 3134 WATER-REACTIVE SOLID, TOXIC, N.O.S. (LITHIUM SULFIDE), 4.3 (6.1), II

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture	
GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)	
Hazard pictograms	
  	
GHS02 GHS05 GHS06	
Signal word Danger	
Hazard statements	
H228 Flammable solid.	
H261 In contact with water releases flammable gas.	
H301 Toxic if swallowed.	
H315 Causes skin irritation.	
H318 Causes serious eye damage.	
H335 May cause respiratory irritation.	
Precautionary statements	
P223 Do not allow contact with water.	
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.	
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.	
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P405 Store locked up.	
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.	
National regulations	
All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.	
All components of this product are listed on the Canadian Non-Domestic Substances List (NDSL).	
SARA Section 313 (specific toxic chemical listings) Substance is not listed.	
California Proposition 65	
Prop 65 - Chemicals known to cause cancer Substance is not listed.	
Prop 65 - Developmental toxicity Substance is not listed.	
Prop 65 - Developmental toxicity, female Substance is not listed.	
Prop 65 - Developmental toxicity, male Substance is not listed.	
Information about limitation of use: For use only by technically qualified individuals.	
Other regulations, limitations and prohibitive regulations	
Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.	
The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.	
Substance is not listed.	
Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.	
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

16 Other information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.	
Department issuing SDS: Global Marketing Department	
Date of preparation/Revision: Print date, revision date and version number are in the header of each page.	
Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)	
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)	
ICAO: International Civil Aviation Organisation	
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
HMIS: Hazardous Materials Identification System (USA)	
WHMIS: Workplace Hazardous Materials Information System (Canada)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
SVHC: Substances of Very High Concern	
vPvB: very Persistent and very Bioaccumulative	
ACGIH: American Conference of Governmental Industrial Hygienists (USA)	
OSHA: Occupational Safety and Health Administration (USA)	
NTP: National Toxicology Program (USA)	
IARC: International Agency for Research on Cancer	
EPA: Environmental Protection Agency (USA)	
Flam. Sol. 1: Flammable solids - Category 1	
Water-react. 2: Substances and mixtures which in contact with water emit flammable gases - Category 2	
Acute Tox. 3: Acute toxicity - Category 3	

(Contd. on page 6)
USA

Product name: *Lithium sulfide*

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. of page 5)