

1 Identification

Product identifier

Product name: Beryllium oxide hydrate

Stock number: A12059

CAS Number:

21883-51-2

EC number:

215-133-1

Index number:

004-003-00-8

Relevant identified uses of the substance or mixture and uses advised against.

Identified use: SU24 Scientific research and development

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Alfa Aesar
Thermo Fisher Scientific Chemicals, Inc.
30 Bond Street
Ward Hill, MA 01835-8099
Tel: 800-343-0660
Fax: 800-322-4757
Email: tech@alfa.com
www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency telephone number:

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

2 Hazard(s) identification

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)



GHS06 Skull and crossbones

Acute Tox. 2 H300 Fatal if swallowed.

Acute Tox. 2 H330 Fatal if inhaled.



GHS08 Health hazard

Carc. 1B H350 May cause cancer.

STOT RE 1 H372 Causes damage to the lung and the blood through prolonged or repeated exposure. Route of exposure: Inhalative.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Hazards not otherwise classified No information known.

Label elements

GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)

Hazard pictograms



GHS06 GHS08

Signal word

Danger

Hazard statements

H300+H330 Fatal if swallowed or if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H335 May cause respiratory irritation.

H372 Causes damage to the lung and the blood through prolonged or repeated exposure. Route of exposure: Inhalative.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P320 Specific treatment is urgent (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

D1A - Very toxic material causing immediate and serious toxic effects

D2A - Very toxic material causing other toxic effects



Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH 3 Health (acute effects) = 3

FIRE 0 Flammability = 0

REACTIVITY 1 Physical Hazard = 1

Product name: Beryllium oxide hydrate	
Other hazards Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.	(Contd. of page 1)
3 Composition/information on ingredients Chemical characterization: Substances CAS# Description: 21883-51-2 Beryllium oxide hydrate Identification number(s): EC number: 215-133-1 Index number: 004-003-00-8	
4 First-aid measures Description of first aid measures General information Immediately remove any clothing soiled by the product. Remove breathing apparatus only after contaminated clothing has been completely removed. In case of irregular breathing or respiratory arrest provide artificial respiration. After inhalation Supply fresh air. If required, provide artificial respiration. Keep patient warm. Seek immediate medical advice. After skin contact Immediately wash with water and soap and rinse thoroughly. Seek immediate medical advice. After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor. After swallowing Do not induce vomiting; immediately call for medical help. Information for doctor Most important symptoms and effects, both acute and delayed No further relevant information available. Indication of any immediate medical attention and special treatment needed No further relevant information available.	
5 Fire-fighting measures Extinguishing media Suitable extinguishing agents Product is not flammable. Use fire-fighting measures that suit the surrounding fire. Special hazards arising from the substance or mixture If this product is involved in a fire, the following can be released: Metal oxide fume Advice for firefighters Protective equipment: Wear self-contained respirator. Wear fully protective impervious suit.	
6 Accidental release measures Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation Environmental precautions: Do not allow material to be released to the environment without proper governmental permits. Methods and material for containment and cleaning up: Dispose of contaminated material as waste according to section 13. Ensure adequate ventilation. Prevention of secondary hazards: No special measures required. Reference to other sections See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for disposal information.	
7 Handling and storage Handling Precautions for safe handling Keep container tightly sealed. Store in cool, dry place in tightly closed containers. Ensure good ventilation at the workplace. Open and handle container with care. Information about protection against explosions and fires: The product is not flammable Conditions for safe storage, including any incompatibilities Storage Requirements to be met by storerooms and receptacles: No special requirements. Information about storage in one common storage facility: Store away from oxidizing agents. Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed containers. Specific end use(s) No further relevant information available.	
8 Exposure controls/personal protection Additional information about design of technical systems: Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Control parameters Components with limit values that require monitoring at the workplace: Beryllium and compounds, as Be ACGIH TLV 0.00005; 0.0002-STEL (inhalable fraction); Confirmed human carcinogen Austria Carcinogen Belgium TWA 0.002; Carcinogen Denmark TWA 0.001; Carcinogen Finland TWA 0.002; 0.006-STEL; Carcinogen France VME 0.002; C2 Carcinogen Germany Carcinogen Hungary 0.001-STEL; Carcinogen	

Product name: Beryllium oxide hydrate

(Contd. of page 2)

Japan OEL 0.002; 2A Carcinogen
Korea TLV 0.002; 0.01-STEL; Confirmed human carcinogen
Netherlands MAC-TGG 0.002; Carcinogen
Norway TWA 0.001
Poland TWA 0.001; 0.003-STEL
Russia 0.001-STEL; Carcinogen
Sweden NGV 0.002; Carcinogen
Switzerland MAK-W 0.002; Carcinogen
United Kingdom TWA 0.002; Carcinogen
USA PEL 0.002

Additional information: No data

Exposure controls

Personal protective equipment

General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Maintain an ergonomically appropriate working environment.

Breathing equipment: Use self-contained respiratory protective device in emergency situations.

Protection of hands:

Impervious gloves

Check protective gloves prior to each use for their proper condition.

The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Penetration time of glove material (in minutes) Not determined

Eye protection: Safety glasses

Body protection: Protective work clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form: Powder

Color: White

Odor: Not determined

Odor threshold: Not determined.

pH-value: Not applicable.

Change in condition

Melting point/Melting range: Not determined

Boiling point/Boiling range: Not determined

Sublimation temperature / start: Not determined

Flash point: Not applicable

Flammability (solid, gaseous) Not determined.

Ignition temperature: Not determined

Decomposition temperature: Not determined

Auto igniting: Not determined.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined

Upper: Not determined

Vapor pressure: Not applicable.

Density: Not determined

Relative density Not determined.

Vapor density Not applicable.

Evaporation rate Not applicable.

Solubility in / Miscibility with

Water: Insoluble

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

dynamic: Not applicable.

kinematic: Not applicable.

Other information No further relevant information available.

10 Stability and reactivity

Reactivity No information known.

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions No dangerous reactions known

Conditions to avoid No further relevant information available.

Incompatible materials: Oxidizing agents

Hazardous decomposition products: Metal oxide fume

11 Toxicological information

Information on toxicological effects

Acute toxicity:

Fatal if swallowed.

Fatal if inhaled.

LD/LC50 values that are relevant for classification: No data

Skin irritation or corrosion: Causes skin irritation.

Eye irritation or corrosion: Causes serious eye irritation.

Sensitization: May cause an allergic skin reaction.

Germ cell mutagenicity: No effects known.

Carcinogenicity:

May cause cancer.

EPA-L: Likely to produce cancer in humans.

IARC-1: Carcinogenic to humans: sufficient evidence of carcinogenicity.

(Contd. on page 4)
USA

Product name: Beryllium oxide hydrate	
(Contd. of page 3)	
ACGIH A1: Confirmed human carcinogen: Agent is carcinogenic to humans based on epidemiologic studies of, or convincing clinical evidence in, exposed humans.	
EPA-K: Known human carcinogens.	
NTP-K: Known to be carcinogenic: sufficient evidence from human studies.	
Reproductive toxicity: No effects known.	
Specific target organ system toxicity - repeated exposure:	
Causes damage to the lung and the blood through prolonged or repeated exposure. Route of exposure: Inhalative.	
Specific target organ system toxicity - single exposure: May cause respiratory irritation.	
Aspiration hazard: No effects known.	
Subacute to chronic toxicity:	
Acute exposure to beryllium may cause dermatitis, chronic skin ulcers, rhinitis, nasopharyngitis, epistaxis, bronchitis, pneumonitis possibly fatal, fever, rales, dyspnea and substernal pain. Chronic exposure causes a delayed form of lung disease which may be delayed for five years or more after exposure stops.	
Symptoms include coughing, shortness of breath, loss of appetite, weight loss and fatigue. Cyanosis is common with elevated pulse and respiratory rates. This disease may progress to death from cardiac or respiratory failure.	
Subacute to chronic toxicity: No effects known.	
Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.	

12 Ecological information

Toxicity	
Aquatic toxicity: No further relevant information available.	
Persistence and degradability No further relevant information available.	
Bioaccumulative potential No further relevant information available.	
Mobility in soil No further relevant information available.	
Additional ecological information:	
General notes:	
Do not allow material to be released to the environment without proper governmental permits.	
Do not allow undiluted product or large quantities to reach ground water, water course or sewage system.	
Avoid transfer into the environment.	
Results of PBT and vPvB assessment	
PBT: Not applicable.	
vPvB: Not applicable.	
Other adverse effects No further relevant information available.	

13 Disposal considerations

Waste treatment methods	
Recommendation Consult state, local or national regulations to ensure proper disposal.	
Uncleaned packagings:	
Recommendation: Disposal must be made according to official regulations.	

14 Transport information

UN-Number DOT, IMDG, IATA	UN1566
UN proper shipping name DOT IMDG, IATA	Beryllium compounds, n.o.s. (Beryllium oxide hydrate) BERYLLIUM COMPOUND, N.O.S. (Beryllium oxide hydrate)
Transport hazard class(es) DOT	
	
Class	6.1 Toxic substances.
Label	6.1
Class	6.1 (T5) Toxic substances
Label	6.1
IMDG, IATA	
	
Class	6.1 Toxic substances.
Label	6.1
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Toxic substances
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Marine Pollutant (DOT):	No
UN "Model Regulation":	UN1566, Beryllium compounds, n.o.s. (Beryllium oxide hydrate), 6.1, II

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture	
GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)	
Hazard pictograms	
	
GHS06 GHS08	
Signal word Danger	
Hazard statements	
H300+H330 Fatal if swallowed or if inhaled.	
H315 Causes skin irritation.	

Product name: **Beryllium oxide hydrate**

(Contd. of page 4)

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H350 May cause cancer.
H335 May cause respiratory irritation.
H372 Causes damage to the lung and the blood through prolonged or repeated exposure. Route of exposure: Inhalative.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P320 Specific treatment is urgent (see on this label).
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.
This product contains a chemical known to the state of California to cause cancer and/or reproductive toxicity.
All components of this product are listed on the Canadian Non-Domestic Substances List (NDSL).

SARA Section 313 (specific toxic chemical listings)

21883-51-2 Beryllium oxide hydrate

California Proposition 65

Prop 65 - Chemicals known to cause cancer

21883-51-2 Beryllium oxide hydrate

Prop 65 - Developmental toxicity Substance is not listed.
Prop 65 - Developmental toxicity, female Substance is not listed.
Prop 65 - Developmental toxicity, male Substance is not listed.

Information about limitation of use:

For use only by technically qualified individuals.
This product contains beryllium and is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Global Marketing Department

Date of preparation / last revision 11/24/2015 / -

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
vPvB: very Persistent and very Bioaccumulative
ACGIH: American Conference of Governmental Industrial Hygienists (USA)
OSHA: Occupational Safety and Health Administration (USA)
NTP: National Toxicology Program (USA)
IARC: International Agency for Research on Cancer
EPA: Environmental Protection Agency (USA)