

# Safety Data Sheet 2116608

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 07/12/2017 Revision date: 11/28/2017 Version: 1.1

# **SECTION 1: Identification**

#### 1.1. Identification

Product form : Substance

Substance name : Trifluoroacetyl chloride

 CAS No
 : 354-32-5

 Product code
 : 2116-6-08

 Formula
 : C2CIF3O

Synonyms : 2,2,2-Trifluoroacetyl chloride

Other means of identification : MFCD00039307

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances Scientific research and development

# 1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

#### 1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

# SECTION 2: Hazard(s) identification

# 2.1. Classification of the substance or mixture

#### Classification (GHS-US)

Simple Asphy H380 - May displace oxygen and cause rapid suffocation Liquefied gas H280 - Contains gas under pressure; may explode if heated

Acute Tox. 1 (Inhalation) H330 - Fatal if inhaled

Skin Corr. 1A H314 - Causes severe skin burns and eye damage

Eye Dam. 1 H318 - Causes serious eye damage STOT SE 3 H335 - May cause respiratory irritation

Aquatic Acute 3 H402 - Harmful to aquatic life

Aquatic Chronic 3 H412 - Harmful to aquatic life with long lasting effects

Full text of H-phrases: see section 16

# 2.2. Label elements

#### **GHS-US** labeling

Hazard pictograms (GHS-US)

Precautionary statements (GHS-US)



GHS04

不多





GHS06

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated

H314 - Causes severe skin burns and eye damage

GHS05

H330 - Fatal if inhaled

H335 - May cause respiratory irritation

H380 - May displace oxygen and cause rapid suffocation H412 - Harmful to aquatic life with long lasting effects

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P284 - In case of inadequate ventilation wear respiratory protection P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

11/28/2017 EN (English US) SDS ID: 2116608 Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/ physician

P320 - Specific treatment is urgent (see supplemental first aid instructions on this label)

P321 - Specific treatment (see supplemental first aid instructions on this label)

P363 - Wash contaminated clothing before reuse

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place P501 - Dispose of contents/container to an approved waste disposal plant

#### 2.3. Other hazards

Other hazards not contributing to the classification

: Lachrymator. May cause frostbite. Reacts violently with water.

# 2.4. Unknown acute toxicity (GHS US)

Not applicable

# SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
Trifluoroacetyl chloride (Main constituent)	(CAS No) 354-32-5	<= 100	Simple Asphy, H380 Liquefied gas, H280 Acute Tox. 1 (Inhalation), H330 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

Full text of H-phrases: see section 16

#### 3.2. Mixture

Not applicable

# **SECTION 4: First aid measures**

First-aid measures after skin contact

# 4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

: Thaw frosted parts with lukewarm water. Do no rub affected area. Remove contaminated clothing and shoes. Get immediate medical advice/attention.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical

advice/attention. Immediately flush eyes thoroughly with water for at least 15 minutes.

First-aid measures after ingestion : Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate

Most important symptoms and effects, both acute and delayed

Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11.

medical advice/attention

Symptoms/injuries after inhalation : May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

Symptoms/injuries after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/injuries after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due

to frostbite from rapid liquid evaporation.

#### 1.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

11/28/2017 EN (English US) SDS ID: 2116608 2/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen chloride. Hydrogen fluoride.

Explosion hazard Contains gas under pressure; may explode if heated. Use water spray or fog for cooling

exposed containers. May form flammable/explosive vapor-air mixture.

#### **Advice for firefighters**

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting Wear gas tight chemically protective clothing in combination with self contained breathing

apparatus. For further information refer to section 8: "Exposure controls/personal protection".

#### **SECTION 6: Accidental release measures**

For non-emergency personnel

# Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

For emergency responders 6.1.2.

6.1.1.

: Do not attempt to take action without suitable protective equipment. For further information Protective equipment

refer to section 8: "Exposure controls/personal protection".

**Emergency procedures** Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

#### **Environmental precautions**

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

## Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up : Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13: "Disposal considerations".

#### Reference to other sections

No additional information available

# SECTION 7: Handling and storage

# Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Handle empty containers with

care because residual vapors are flammable. Close valve after each use and when empty.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good

ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Safe handling of the gas receptacle : Securely chain cylinders when in use and protect against physical damage.

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or Hygiene measures

smoke when using this product. Always wash hands after handling the product.

# Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed Storage conditions

when not in use. Moisture sensitive. Keep away from ignition sources.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

# SECTION 8: Exposure controls/personal protection

#### Control parameters

No additional information available

11/28/2017 EN (English US) SDS ID: 2116608 3/8

# Safety Data Sheet

Skin and body protection

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released. Gas detectors should be used when toxic gases may be

released.

Hand protection : Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

: Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

: No data available

Thermal hazard protection : Cold insulating gloves.

Other information : Safety shoes. 29 CFR 1910.136: Foot Protection.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state : Gas

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available

Melting point : -146 °C

Freezing point : No data available

Boiling point : -18 °C

Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available : No data available Flammability (solid, gas) **Explosion limits** No data available : No data available Explosive properties Oxidizing properties : No data available Vapor pressure : No data available Relative density : No data available Relative vapor density at 20 °C No data available Molecular mass : 132.47 a/mol Solubility : No data available Log Pow : No data available Auto-ignition temperature : No data available : No data available Decomposition temperature Viscosity No data available : No data available Viscosity, kinematic

# 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Viscosity, dynamic

No additional information available

# 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

# 10.3. Possibility of hazardous reactions

Reacts violently with water.

#### 10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame. Return of water into the container must be prevented.

11/28/2017 EN (English US) SDS ID: 2116608 4/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 10.5. Incompatible materials

Alcohols. Alkali metals. Bases. Oxidizing agents. Water.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

# **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity : Inhalation: Fatal if inhaled.

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous

membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

Symptoms/injuries after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/injuries after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due

to frostbite from rapid liquid evaporation.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

No additional information available

# 12.2. Persistence and degradability

No additional information available

## 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

# 12.5. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

# **SECTION 14: Transport information**

### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN3057 Trifluoroacetyl chloride, 2.3

UN-No.(DOT) : UN3057

Proper Shipping Name (DOT) : Trifluoroacetyl chloride

Transport hazard class(es) (DOT) : 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115

11/28/2017 EN (English US) SDS ID: 2116608 5/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) 2.3 - Poison gas 8 - Corrosive





DOT Packaging Non Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 314;315 DOT Special Provisions (49 CFR 172.102)

: 2 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone B (see 173.116(a) or 173.133(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter.

B7 - Safety relief devices are not authorized on multi-unit tank car tanks. Openings for safety relief devices on multi-unit tank car tanks shall be plugged or blank flanged.

B9 - Bottom outlets are not authorized.

B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not promote corrosion to steel when wet.

T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.

TP21 - The wall thickness must not be less than 8 mm. Portable tanks must be hydraulically

tested and internally inspected at intervals not exceeding 2.5 years.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : Forbidden

CFR 175.75)

**DOT Vessel Stowage Location** : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel

carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

**DOT Vessel Stowage Other** : 40 - Stow "clear of living quarters"

Emergency Response Guide (ERG) Number

Other information : No supplementary information available.

# **TDG**

No additional information available

# Transport by sea

UN-No. (IMDG) : 3057

Proper Shipping Name (IMDG) : TRIFLUOROACETYL CHLORIDE

Class (IMDG) : 2 - Gases

# Air transport

UN-No. (IATA) : 3057

Proper Shipping Name (IATA) : Trifluoroacetyl chloride

Class (IATA)

# **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

#### Trifluoroacetyl chloride (354-32-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

11/28/2017 EN (English US) SDS ID: 2116608 6/8

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# 15.2. International regulations

#### **CANADA**

# Trifluoroacetyl chloride (354-32-5)

Listed on the Canadian NDSL (Non-Domestic Substances List)

No additional information available

#### **National regulations**

# Trifluoroacetyl chloride (354-32-5)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law)

#### 15.3. US State regulations

	.o. oo otate regulations		
Trifluoroacetyl chloride (354-32-5)			
	State or local regulations	U.S New Jersey - Right to Know Hazardous Substance List	

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

# **SECTION 16: Other information**

Revision date : 11/28/2017

#### Full text of H-phrases:

ext of Fi-philases.	
Acute Tox. 1 (Inhalation)	Acute toxicity (inhalation) Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Liquefied gas	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
Skin Corr. 1A	Skin corrosion/irritation Category 1A
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H280	Contains gas under pressure; may explode if heated
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H330	Fatal if inhaled
H335	May cause respiratory irritation
H380	May displace oxygen and cause rapid suffocation
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard

: 4 - Very short exposure could cause death or serious residual injury even though prompt medical attention was

NFPA fire hazard

: 0 - Materials that will not burn.

NFPA reactivity

2 - Normally unstable and readily undergo violent decomposition but do not detonate. Also: may react violently with water or may form potentially explosive

mixtures with water.

NFPA specific hazard

: W - Unusual reactivity with water. This indicates a potential hazard using water to fight a fire involving this material. When a compound is both water-reactive and an oxidizer, the W/bar symbol should go in this quadrant and the OX warning is placed immediately below the NFPA diamond.



HMIS III Rating

Health

: 4 Severe Hazard - Life-threatening, major or permanent damage may result from single or repeated overexposures

Flammability

: 0 Minimal Hazard - Materials that will not burn

Physical

: 2 Moderate Hazard - Materials that are unstable and may undergo violent chemical changes at normal temperature and pressure with low risk for explosion. Materials may react violently with water or form peroxides upon exposure to air.

11/28/2017 EN (English US) SDS ID: 2116608 7/8

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

11/28/2017 SDS ID: 2116608 EN (English US) 8/8