

1,1,1,3,3-Pentafluorobutane

Safety Data Sheet 1100355

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 04/29/2016

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Substance
 Substance name : 1,1,1,3,3-Pentafluorobutane
 CAS No : 406-58-6
 Product code : 1100-3-55
 Formula : C4H5F5
 Other means of identification : MFCD03094115

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals
 Manufacture of substances
 Scientific research and development

1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.
 P.O. Box 309
 Alachua, FL 32615 - United States of America
 T (386) 462-0788 - F (386) 462-7097
info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 2 H225 - Highly flammable liquid and vapour
 Skin Irrit. 2 H315 - Causes skin irritation
 Eye Irrit. 2A H319 - Causes serious eye irritation
 STOT SE 3 H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02



GHS07

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H335 - May cause respiratory irritation

Precautionary statements (GHS-US) :

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
 P233 - Keep container tightly closed
 P240 - Ground/bond container and receiving equipment
 P241 - Use explosion-proof electrical/ventilating/lighting equipment
 P242 - Use only non-sparking tools
 P243 - Take precautionary measures against static discharge
 P261 - Avoid breathing fumes, gas, mist, spray, vapors
 P264 - Wash skin thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P302+P352 - If on skin: Wash with plenty of soap and water
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

1,1,1,3,3-Pentafluorobutane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor/physician if you feel unwell
P321 - Specific treatment (see supplemental first aid instructions on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
1,1,1,3,3-Pentafluorobutane (Main constituent)	(CAS No) 406-58-6	<= 100	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get medical advice/attention.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride.

Explosion hazard : Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

1,1,1,3,3-Pentafluorobutane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.
- 6.1.1. For non-emergency personnel**
- Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.
- 6.1.2. For emergency responders**
- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.
- Methods for cleaning up : Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.
- Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.
- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.
- Safe handling of the gas receptacle : Securely chain cylinders when in use and protect against physical damage.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Keep away from ignition sources.
- Incompatible materials : Refer to Section 10 on Incompatible Materials.
- Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularly checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.
- Hand protection : Protective gloves. 29 CFR 1910.138: Hand Protection.
- Eye protection : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.

1,1,1,3,3-Pentafluorobutane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 40 °C
Flash point	: -27 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 326.0 mm Hg (@ 20 °C)
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.27 g/ml (@ 20 °C)
Molecular mass	: 148.07 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, sparks and flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

1,1,1,3,3-Pentafluorobutane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s., 3, II

UN-No.(DOT) : UN1993

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

1,1,1,3,3-Pentafluorobutane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F). TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Other information	: No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG)	: 1993
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S.
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger

Air transport

UN-No. (IATA)	: 1993
Proper Shipping Name (IATA)	: Flammable liquid, n.o.s.
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

1,1,1,3,3-Pentafluorobutane (406-58-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

1,1,1,3,3-Pentafluorobutane (406-58-6)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

1,1,1,3,3-Pentafluorobutane (406-58-6)

Listed on ELINCS (European List of Notified Chemical Substances)

1,1,1,3,3-Pentafluorobutane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

1,1,1,3,3-Pentafluorobutane (406-58-6)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on Turkish inventory of chemical

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation

NFPA health hazard


: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable for any damage resulting from handling or from contact with the above product.