



EREZTECH LLC
11555 Medlock Bridge Road, Suite 100, Johns Creek, GA 30097, USA
T: +1.888.658.1221 F: 1.678.619.2020
E: info@ereztech.com W: <https://ereztech.com>

SAFETY DATA SHEET

Section 1. Identification

Product Name: Tungsten(VI) ethoxide
Product Type: Solid
CAS Number: 62571-53-3
Product Number: [W1533](#)
Product Manufacturer: Ereztech LLC
11555 Medlock Bridge Road, Suite 100
Johns Creek, GA 30097
Product Information: (888) 658-1221
In Case of an Emergency: CHEMTREC: 1-800-424-9300 (USA);
+1 703-527-3887 (International); CCN836180
*** Contact manufacturer for all non-emergency calls.

Section 2. Hazards Identification

Appearance/Odor: Off-white to brown solid, odor not determined.
Classification: FLAMMABLE SOLID – Category 2, H228
SKIN CORROSION/IRRITATION; - Category 2, H315
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A, H319
SPECIFIC ORGAN TOXICITY, SINGLE EXPOSURE; RESPIRATORY
TRACT IRRITATION; - Category 3, H335

GHS Label Elements

Signal Word: WARNING.
Hazard Statements: H228: Flammable solid.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.

Hazard Pictograms:



Tungsten(VI) ethoxide

Safety Data Sheet

Section 2. Hazards Identification

Precautionary Statements

Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P240: Ground/Bond container and receiving equipment.
P241: Use explosion proof electrical/ventilating/lighting/processing equipment.
P261: Avoid breathing dust.
P264: Wash skin thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.
P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present. Continue rinsing.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P332 + P313: If skin irritation occurs: Get medical advice/attention.
P337 + P313: If eye irritation persists: Get medical advice/attention.
P362: Take off contaminated clothing and wash before reuse.
P370 + P378: In case of fire: Use water spray, foam, dry chemical or carbon dioxide (CO₂) for extinction.

Storage:

P403 + P233: Store in a well ventilated place. Keep container tightly closed.

Disposal:

P405: Store locked up.
P501: Dispose of contents/ container to an approved waste disposal plant.

OSHA/HCS status:

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Hazards Not Otherwise Classified (HNOC):

Reacts with water to release ethanol.

Section 3. Composition/Information on Ingredients

Substances

Formula

: C₁₂H₃₀O₆W

Molecular Weight

: 454.21 g/mol

CAS-No.

: 62571-53-3

Synonyms

: Hexaethoxytungsten; "ethanolate; tungsten" (IUPAC).

Tungsten(VI) ethoxide

Safety Data Sheet

Section 3. Composition/Information on Ingredients

Ingredient Name	%	CAS Number
Tungsten(VI) ethoxide	99	62571-53-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First Aid Measures

Description of Necessary First Aid Measures

- General Advice:** Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
- Eye Contact:** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue rinsing. Get immediate medical attention.
- Skin Contact:** Wash off contaminated skin with soap and plenty of water. Get immediate medical attention.
- Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Call a POISON CENTER or doctor/physician immediately.
- Ingestion:** Call a physician or POISON CONTROL CENTER immediately. Rinse mouth. Do NOT induce vomiting. Remove dentures if any. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Consult a physician.

Most Important Symptoms/Effects, Acute And Delayed Potential Acute Health Effects

- Eye Contact:** Product causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling and blurred vision.
- Inhalation:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Skin Contact:** Causes skin irritation. Symptoms may include redness, itching and pain.
- Ingestion:** May be harmful if swallowed.

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

Notes to Physician: This product reacts with water in the acid contents of the stomach to produce ethanol.

Specific Treatments: No specific treatment.

Tungsten(VI) ethoxide

Safety Data Sheet

Section 4. First Aid Measures

Protection of First Responders: No action taken shall be taken involving any personal risk without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire Fighting Measures

General Hazards: None identified.

Suitable Extinguishing Media: Use foam, dry chemical or carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use water jet. Water spray may be ineffective due to the release of ethanol from product hydrolysis.

Unusual Fire and Explosion Hazards: This material reacts with water and compounds containing active hydrogen such as alcohols and acids to produce ethanol. Product runoff to sewer may create a fire or explosion hazard. Ethanol vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to an ignition source and flashback.

Product of Combustion: Decomposition products include ethanol, organic acid vapors, carbon oxides (CO, CO₂) and tungsten oxides.

Protection of Firefighters: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Avoid contact with skin or eyes. Avoid the formation and inhalation of dusts, aerosols, vapors and gases. Eliminate all local and distant ignition sources. Move containers from fire area if process can be accomplished without risk to firefighters. Use a water spray or fog to cool unopened containers. Fire-fighters should wear appropriate protection equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material.

Tungsten(VI) ethoxide

Safety Data Sheet

Section 6. Accidental Release Measures

For Non-Emergency Personnel: (cont.)

Avoid exposure to water and the formation of dusts and aerosols. Avoid inhalation of dusts, aerosols, gases and vapors. Provide adequate ventilation. Wear respiratory protection. Put on appropriate personal protective equipment.

For Emergency Responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental Precautions:

Do not allow dispersal of spilled material and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for Containment

Small Spill:

Eliminate all ignition sources. Move containers from spill area if safe to do so. Contain and collect spillage using a dry, inert binding material (sand, clay, diatomaceous earth), place in an appropriate waste disposal container and seal. Avoid contact with water/moisture and the creation of dusts and aerosols. Avoid the inhalation of dusts and aerosols. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large Spill:

Eliminate all ignition sources. Move containers from spill area if safe to do so. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, dry binding material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in dry, sealed container for disposal according to local regulations (see Section 13). Avoid contact with water/moisture and the creation/inhalation of dusts and aerosols. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

Section 7. Handling and Storage

Precautions:

Product is moisture sensitive. Handle under a dry, inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Keep away from all sources of ignition – NO SMOKING. Take precautions to prevent buildup of static charge. Avoid contact with water.

Tungsten(VI) ethoxide

Safety Data Sheet

Section 7. Handling and Storage

Precautions (cont.):

Avoid contact with skin, eyes and clothing. Avoid formation and inhalation of dusts and aerosols. Do not ingest. Provide adequate ventilation.

Protective Measures:

Put on appropriate personal protective equipment (see Section 8). Keep in the original container kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

General Occupational Hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Safe Storage Conditions:

Product is moisture sensitive. Handle and store under an inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Keep away from air, moisture, heat, sparks and open flames. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (oxidizing agents) and food and drink. Keep container tightly closed and sealed until ready for use. Store locked up.

Section 8. Exposure Controls/Personal Protection

Introductory Remarks:

These recommendations provide general guidance for handling this product. Because work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and conduct regular repairs. Waste from these procedures should be handled in accordance with Section 13.

Occupational Exposure Limits

List	Components	CAS-No.	Type	Value
ACGIH	Tungsten(VI) ethoxide	62571-53-3	TLV	5.0 mg/m ³ as W TWA
			TLV	10.0 mg/m ³ as W STEL
NIOSH	Tungsten(VI) ethoxide	62571-53-3	REL	5.0 mg/m ³ as W TWA
			REL	10.0 mg/m ³ as W ST

Tungsten(VI) ethoxide

Safety Data Sheet

Section 8. Exposure Controls/Personal Protection

Engineering Controls:

Properly operating explosion-proof, chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Provide an eyewash/shower station.

Environmental Exposure Controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures

Hygiene Measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Remove all soiled and contaminated clothing immediately. Do not inhale dusts or aerosols. Avoid contact with eyes and skin. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to aerosols or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles, faceshield (8-inch minimum). Refer to 29 CFR 1910.133, ANSI Z87.1, or European Standard EN166.

Skin Protection

Hand Protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Chemical-resistant gloves. For full contact, wear Neoprene or nitrile rubber gloves.

Tungsten(VI) ethoxide

Safety Data Sheet

Section 8. Exposure Controls/Personal Protection

Hand Protection (cont.):

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Other Skin Protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Section 9. Physical and Chemical Properties

Physical State:

Solid.

Color:

Off-white to brown.

Odor:

No data available.

Odor Threshold:

No data available.

pH:

No data available.

Melting Point:

150 °C (302 °F).

Boiling Point:

No data available.

Flash Point:

No data available.

Flammability (solid):

No data available.

Specific Gravity:

No data available.

Vapor Pressure:

No data available.

Vapor Density:

No data available.

Water Solubility:

Reacts with water to release ethanol.

Section 10. Stability and Reactivity

Reactivity:

No data available.

Chemical Stability:

Stable at normal ambient temperature and pressure and under recommended storage conditions.

Tungsten(VI) ethoxide

Safety Data Sheet

Section 10. Stability and Reactivity

Conditions to Avoid:	Exposure to water/moisture, heat, flames, sparks.
Incompatible Materials:	Water/moisture, oxidizing agents.
Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products formed under fire conditions: ethanol, organic acid vapors, carbon oxides and metal oxide fumes. In the event of a fire: see section 5.
Possibility of Hazardous Reactions:	Reacts with water to produce ethanol.

Section 11. Toxicological Information

Information on Toxicological Effects

Acute Toxicity	: No specific data available.
Irritation/Corrosion	: Causes skin irritation. Cause serious eye irritation.
Sensitization	: No specific data available.
Germ Cell Mutagenicity	: No effects known.
Carcinogenicity	
IARC	: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH.
NTP	: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.
OSHA	: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by OSHA.
Reproductive Toxicity	: This product is not expected to cause reproductive or developmental effects.
Teratogenicity	: No specific data available.
Specific Target Organ Toxicity (Single Exposure)	: Inhalation – May cause respiratory tract irritation.
Specific Target Organ Toxicity (Repeated Exposure)	: No specific data available.
Aspiration Hazard	: No specific data available.

Tungsten(VI) ethoxide

Safety Data Sheet

Section 11. Toxicological Information

Information on the Likely Routes of Exposure

: No specific data available.

Additional Information

: May be harmful if inhaled, ingested or absorbed through the skin. On contact with water, this product releases ethanol which may have a chronic effect on the Central Nervous System (CNS).

To the best of our knowledge, the chemical, physical, toxicological and ecological properties of this product have not been fully investigated.

Section 12. Ecological Information

Numerical Measures of Toxicity

Toxicity to Fish

: No specific data available.

Toxicity to Daphnia and Other Aquatic Invertebrates

: No specific data available.

Toxicity to Algae

: No specific data available.

Persistence and Degradability

Biodegradability

: No specific data available.

Bioaccumulative Potential

: No specific data available.

Mobility in Soil

: No specific data available.

Other Adverse Effects

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13. Disposal Considerations

Waste Treatment Methods

Product

Dispose of in accordance with local, state, and federal regulations. Refer to 40 CFR 260-299 for complete waste disposal regulations. Consult your local, state, or federal agency before disposing of any chemicals.

Contaminated Packaging

Empty containers retain product residue (dusts and vapors) and can be dangerous. DO NOT EXPOSE CONTAINERS TO MOISTURE, HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Tungsten(VI) ethoxide

Safety Data Sheet

Section 14. Transport Information

	DOT	IMDG	IATA
UN Number	UN 3181	UN 3181	UN 3181
UN Proper Shipping Name	Metal salts of organic compounds, flammable, n.o.s. (Tungsten(VI) ethoxide)	METAL SALTS OF ORGANIC COMPOUNDS, FLAMMABLE, N.O.S. (Tungsten(VI) ethoxide)	Metal salts of organic compounds, flammable, n.o.s. (Tungsten(VI) ethoxide)
Transport Hazard Classes	4.1	4.1	4.1
Packing Group	III	III	III
Environmental Hazards	No	No	No
Additional Information	-	EMS-No: F-A, S-G	-

Special Precautions for User

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transporting in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

Section 15. Regulatory Information

TSCA (Toxic Substance Control Act):

This product is not listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory). Use of this product is restricted to research and development only. This product must be used under the supervision of a technically qualified individual as defined by the TSCA. This product must not be used for commercial purposes or in formulations for commercial purposes.

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard (Flammable solid), Acute Health Hazard (Skin corrosion or irritation; Serious eye damage or eye irritation; Specific target organ toxicity, single exposure: respiratory tract irritation.

Tungsten(VI) ethoxide

Safety Data Sheet

Section 15. Regulatory Information

Massachusetts Right to Know Components

No components are subject to Massachusetts Right to Know Act.

Pennsylvania Right to Know Components

No components are subject to Pennsylvania Right to Know Act.

New Jersey Right to Know Components

No components are subject to New Jersey Right to Know Act.

California Proposition 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Section 16. Other Information

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

HMIS Rating

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	0

Tungsten(VI) ethoxide

Safety Data Sheet

Section 16. Other Information

History

Date of Printing : 2/21/2020
Date of Issue/Date of Revision : 2/21/2020
Date of Previous Issue : 1/25/2020
References : None available.

Abbreviations and Acronyms

ACGIH: American Conference of Governmental Industrial Hygienists.
ATE: Acute Toxicity Estimate
CAS: Chemical Abstracts Service (division of the American Chemical Society).
DOT: US Department of Transportation.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
HMIS: Hazardous Materials Identification System.
IARC: International Agency for Research on Cancer.
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA).
IDLH: Immediately Dangerous to Life or Health (US National Institute for Occupation Health and Safety (NIOSH)).
IMDG: International Maritime Code for Dangerous Goods.
NFPA: National Fire Protection Association.
NIOSH: National Institute of Occupational Safety and Health.
NTP: National Toxicology Program.
OSHA: Occupational Safety and Health Administration.
PEL: Permissible Exposure Limits.
REL: Recommended Exposure Limits.
SARA: Superfund Amendments and Reauthorization Act.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limit Values (ACGIH).
TWA: Time Weighted Average.
VOC: Volatile Organic Compound.

Disclaimer

The information herein is believed to be accurate and is presented in good faith; however, no warranties or representations are made by Ereztech LLC regarding the accuracy or completeness of the information. Ereztech LLC shall not be liable for any damages resulting from the handling, or from the contact with the above product.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.