

SAFETY DATA SHEET

Version 6.4 Revision Date 02/07/2023 Print Date 05/06/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Ethan(ol-d)

Product Number : 151904 Brand : Aldrich

Index-No. : 603-002-00-5 CAS-No. : 925-93-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapor.



H319	Causes serious eye irritation.
Precautionary statement(s)	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash skin thoroughly after handling.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Ethyl alcohol-d1 Ethanol-OD

Component	Classification	Concentration
ethyl alcohol-d1 (O-deuterated)		
	Flam. Liq. 2; Eye Irrit. 2A; H225, H319 Concentration limits: >= 50 %: Eye Irrit. 2A, H319;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.



SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
ethyl alcohol-d ₁ (O-deuterated)	925-93-9	STEL	1,000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Confirmed animal carcinogen with unknown relevance to humans		



TWA	1,000 ppm 1,900 mg/m3	USA. NIOSH Recommended Exposure Limits
TWA	1,000 ppm 1,900 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
PEL	1,000 ppm 1,900 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
TWA	1,000 ppm 1,900 mg/m3	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm Break through time: 480 min

Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 120 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.



SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

a) Appearance Form: liquid, clear

Color: colorless

alcohol-like b) Odor

c) Odor Threshold No data available No data available d) pH

Melting point/range: -114 °C (-173 °F) - lit. e) Melting point/freezing point

f) Initial boiling point 78 °C 172 °F - lit. and boiling range

14.0 °C (57.2 °F) - closed cup g) Flash point

h) Evaporation rate No data available No data available Flammability (solid, gas)

j) Upper/lower Upper explosion limit: 19 %(V) flammability or Lower explosion limit: 3.3 %(V) explosive limits

k) Vapor pressure 59.5 hPa at 20.0 °C (68.0 °F)

 Vapor density No data available

0.806 g/mL at 25 °C (77 °F) m) Density

Relative density No data available completely soluble n) Water solubility o) Partition coefficient: No data available n-octanol/water

p) Autoignition 363.0 °C (685.4 °F) temperature

q) Decomposition No data available temperature

No data available r) Viscosity s) Explosive properties No data available

t) Oxidizing properties none

Other safety information 9.2

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion/exothermic reaction with:

hydrogen peroxide

perchlorates

perchloric acid

Nitric acid

mercury(II) nitrate

permanganic acid

Nitriles

peroxi compounds

Strong oxidizing agents

nitrosyl compounds

Peroxides

sodium

Potassium

halogen oxides

calcium hypochlorite

nitrogen dioxide

metallic oxides

uranium hexafluoride

iodides

Chlorine

Alkali metals

Alkaline earth metals

alkali oxides

Ethylene oxide

silver

with

Nitric acid

silver compounds

with

Ammonia

potassium permanganate

with

conc. sulfuric acid

Risk of ignition or formation of inflammable gases or vapours with:

halogen-halogen compounds

chromium(VI) oxide

chromyl chloride

Fluorine

hydrides

Oxides of phosphorus

platinum

Nitric acid

with

potassium permanganate

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

rubber, various plastics

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 10,470 mg/kg

(OECD Test Guideline 401)

Remarks: The value is given in analogy to the following substances: ethanol

LC50 Inhalation - Rat - male and female - 4 h - 124.7 mg/l - vapor

(OECD Test Guideline 403)

Remarks: The value is given in analogy to the following substances: ethanol

Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 24 h (OECD Test Guideline 404)

Remarks: The value is given in analogy to the following substances: ethanol

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation.

(OECD Test Guideline 405)

Remarks: The value is given in analogy to the following substances: ethanol

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Remarks: The value is given in analogy to the following substances: Methanol

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Remarks: The value is given in analogy to the following substances: ethanolTest Type: In

vitro mammalian cell gene mutation test Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Remarks: The value is given in analogy to the following substances: ethanol

Test Type: dominant lethal test

Species: Mouse

Application Route: Oral

Method: OECD Test Guideline 478

Result: Positive results were obtained in some in vivo tests.

Remarks: The value is given in analogy to the following substances: ethanol

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male - Oral - NOAEL (No observed adverse effect level) - 1,730 mg/kg - LOAEL (Lowest observed adverse effect level) - 3,200 mg/kg Remarks: The value is given in analogy to the following substances: ethanol

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria, Nausea, Vomiting

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Heart - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) -

15,300 mg/l - 96 h

(US-EPA)

Remarks: The value is given in analogy to the following substances:

ethanol

Toxicity to daphnia

and other aquatic invertebrates

static test LC50 - Ceriodaphnia dubia (water flea) - 5,012 mg/l - 48

h

Remarks: (ECHA)

The value is given in analogy to the following substances: ethanol

Toxicity to algae static test ErC50 - Chlorella vulgaris (Fresh water algae) - 275 mg/l

- 72 h

(OECD Test Guideline 201)

Remarks: The value is given in analogy to the following substances:

ethanol



Toxicity to bacteria static test IC50 - activated sludge - > 1,000 mg/l - 3 h

(OECD Test Guideline 209)

Remarks: The value is given in analogy to the following substances: ethanolThe value is given in analogy to the following substances:

Methanol

Toxicity to semi-static test NOEC - Danio rerio (zebra fish) - 250 mg/l - 120 h

fish(Chronic toxicity) Remarks: (ECHA)

The value is given in analogy to the following substances: ethanol

Toxicity to daphnia semi-static test NOEC - Daphnia magna (Water flea) - 9.6 mg/l - 9 d

and other aquatic Remarks: (ECHA)

invertebrates(Chronic The value is given in analogy to the following substances: ethanol

toxicity)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 15 d

Result: ca.95 % - Readily biodegradable.

(OECD Test Guideline 301E)

Remarks: The value is given in analogy to the following substances:

ethanol

Biochemical Oxygen 930 - 1,670 mg/g Demand (BOD) Remarks: (Lit.)

Theoretical oxygen 2,100 mg/g demand Remarks: (Lit.)

12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.



SECTION 14: Transport information

DOT (US)

UN number: 1170 Class: 3 Packing group: II

Proper shipping name: Ethanol Reportable Quantity (RQ):

Poison Inhalation Hazard: No

IMDG

UN number: 1170 Class: 3 Packing group: II EMS-No: F-E, S-D

Proper shipping name: ETHANOL

IATA

UN number: 1170 Class: 3 Packing group: II

Proper shipping name: Ethanol

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

ethyl alcohol-d ₁ (O-deuterated)	CAS-No. 925-93-9	Revision Date 1993-04-24
,		

Pennsylvania Right To Know Components

ethyl alcohol-d1 (O-deuterated)	CAS-No.	Revision Date
	925-93-9	1993-04-24

California Prop. 65 Components

, which is/are known to the State of California to	CAS-No.	Revision Date
cause cancer and birth defects or other reproductive	925-93-9	2011-05-20
harm. For more information go to		
www.P65Warnings.ca.gov.ethyl alcohol-d1 (O-		
deuterated)		

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of



the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

Details in analogy to the undeuterated compound.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.4 Revision Date: 02/07/2023 Print Date: 05/06/2023

