1 Identification

Product identifier

Product name: Ethyl vinyl ether

Stock number: A15691 CAS Number:

109-92-2

EC number: 203-718-4

Relevant identified uses of the substance or mixture and uses advised against.

Identified use: SU24 Scientific research and development

Details of the supplier of the safety data sheet

Details of the supplier of the safety da Manufacturer/Supplier:
Alfa Aesar
Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street
Ward Hill, MA 01835-8099
Tel: 800-343-0660
Fax: 800-322-4757

Email: tech@alfa.com www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency telephone number:

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

2 Hazard(s) identification

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)



GHS02 Flame

Flam. Liq. 1 H224 Extremely flammable liquid and vapour.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. Hazards not otherwise classified No information known.

GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS) Hazard pictograms







Signal word Danger **Hazard statements** H224 Extremel

Hazar Statementy flammable liquid and vapour. H319 Causes serious eye irritation. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements
P210 Keep aw.
P261 Avoid bre
P280 Wear pro
P240 Ground/b

Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

B2 - Flammable liquid D2B - Toxic material causing other toxic effects



Classification system HMIS ratings (scale 0-4) (Hazardous Materials Identification System)



Health (acute effects) = 1
Flammability = 4
Physical Hazard = 2

Other hazards Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Substances CAS# Description:
109-92-2 Ethyl vinyl ether Concentration: ≤100%

Product name: Ethyl vinyl ether

(Contd. of page 1)

Identification number(s): EC number: 203-718-4 Impurities and stabilizing additives: Stabilizer is present but may vary.

4 First-aid measures

Description of first aid measures

After inhalation

Arter Infratation Supply fresh air. If required, provide artificial respiration. Keep patient warm. Seek immediate medical advice.

After skin contact Immediately wash with water and soap and rinse thoroughly.

Seek immediate medical advice.

After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing Seek medical treatment.

Information for doctor

Most important symptoms and effects, both acute and delayed Causes serious eye irritation.

May cause respiratory irritation. May cause drowsiness or dizziness

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents Carbon dioxide, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

If this product is involved in a fire, the following can be released:

Carbon monoxide and carbon dioxide

Advice for firefighters

Protective equipment:
Wear self-contained respirator.
Wear fully protective impervious suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Environmental precautions: Do not allow product to reach sewage system or any water course.
Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

Prevention of secondary hazards: Keep away from ignition sources.

Reference to other sections
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

Handling
Precautions for safe handling
Keep container tightly sealed.
Store in cool, dry place in tightly closed containers.
Keep away from heat and direct sunlight.

Ensure good ventilation at the workplace. Open and handle container with care.

Information about protection against explosions and fires:
Protect against electrostatic charges.
Fumes can combine with air to form an explosive mixture.
Keep ignition sources away.

Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility:

Do not store together with acids.

Store away from oxidizing agents.

Further information about storage conditions:
Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
Protect from heat and direct sunlight.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems:
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring at the workplace:
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
Additional information: No data

Exposure controls
Personal protective equipment
General protective and hygienic measures
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Remove all soiled and contaminated clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skip

Avoid contact with the eyes and skin. Maintain an ergonomically appropriate working environment. **Breathing equipment:** Use suitable respirator when high concentrations are present.

(Contd. on page 3)

Product name: Ethyl vinyl ether

(Contd. of page 2)

Recommended filter device for short term use:

Use a respirator with multi-purpose combination (US) or type AXBEK (EN 14387) as a backup to engineering controls. Risk assessment should be performed to determine if air-purifying respirators are appropriate. Only use equipment tested and approved under appropriate government standards such as NIOSH (USA) or CEN (EU).

Product is not explosive. However, formation of explosive air/vapor mixtures is possible.

Protection of hands:

Liquid Ether-like

Not determined.

Not determined.

-45 °C (-49 °F) Not determined.

200 °C (392 °F) Not determined

Not determined.

Not determined.

Not determined.

-115 °C (-175 °F) 33-34 °C (91-93 °F) Not determined

Impervious gloves
Check protection of names:
Impervious gloves
Check protective gloves prior to each use for their proper condition.
The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Material of gloves Fluorocarbon rubber (Viton)
Penetration time of glove material (in minutes) >30
Glove thickness 0.7 mm
Eye protection: Safety glasses
Body protection: Protective work clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties General Information

Appearance: Form: Odor:

Odor threshold: pH-value:

Change in condition Melting point/Melting range: Boiling point/Boiling range: Sublimation temperature / start:

Flash point: Flammability (solid, gaseous) Ignition temperature: Decomposition temperature: Auto igniting:

Danger of explosion: Explosion limits: Lower: Upper:

Vapor pressure at 20 °C (68 °F): Density at 20 °C (68 °F): Relative density Vapor density

Evaporation rate Solubility in / Miscibility with

Water: Not miscible or difficult to mix Partition coefficient (n-octanol/water): Not determined.

Viscosity: dynamic: Not determined

kinematic: Other information

1.35 Vol % 12 Vol % 533 hPa (400 mm Hg) 0.754 g/cm³ (6.292 lbs/gal) Not determined.

Not determined. No further relevant information available.

10 Stability and reactivity

Reactivity No information known.
Chemical stability Stable under recommended storage conditions.
Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.
Possibility of hazardous reactions Reacts with strong oxidizing agents
Conditions to avoid No further relevant information available.

Incompatible materials:

Oxidizing agents

Hazardous decomposition products: Carbon monoxide and carbon dioxide

Additional information: Avoid loss of stabilizer.

11 Toxicological information

Information on toxicological effects
Acute toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains acute toxicity data for this substance

LD/LC50 values that are relevant for classification:

LD50 8160 μL/kg (rat) Oral Dermal LD50 >20 gm/kg (rat)

>20 mL/kg (rabbit)

Skin irritation or corrosion: Repeated exposure may cause skin dryness or cracking.

Eye irritation or corrosion: Causes serious eye irritation.

Sensitization: No sensitizing effects known.

Germ cell mutagenicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains mutation data for this substance.

Carcinogenicity: No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

Reproductive toxicity: No effects known.

Reproductive toxicity: No effects known.

Specific target organ system toxicity - repeated exposure: No effects known.

Specific target organ system toxicity - single exposure:

May cause drowsiness or dizziness.

May cause respiratory irritation.

Aspiration hazard: No effects known.

Subacute to chronic toxicity: No effects known.

Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

Carcinogenic categories
OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

12 Ecological information

Toxicity Aquatic toxicity: No further relevant information available.

(Contd. on page 4)

(Contd. of page 3)

Product name: Ethyl vinyl ether

Persistence and degradability No further relevant information available. Bioaccumulative potential No further relevant information available. Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities to reach ground water, water course or sewage system.

Do not allow undiffuled product or large quantities to reach groun Avoid transfer into the environment.

Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.
Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods
Recommendation Consult state, local or national regulations to ensure proper disposal.
Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.

14 Transport	information
--------------	-------------

UN-Number DOT, IMDG, IATA	UN1302
UN proper shipping name DOT ADR IMDG IATA	Vinyl ethyl ether, stabilized 1302 Vinyl ethyl ether, stabilized VINYL ETHYL ETHER STABILIZED

Transport hazard class(es)

DOT



3 Flammable liquids.



3 (F1) Flammable liquids Label IMDG, IATA



Class 3 Flammable liquids. Label

Packing group DOT, ADR, IMDG, IATA

Environmental hazards: Not applicable.

Special precautions for user EMS Number: Warning: Flammable liquids F-E,S-D

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

DOT

Marine Pollutant (DOT):

No

UN "Model Regulation": UN1302, Vinyl ethyl ether, stabilized, 3, I

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS) Hazard pictograms





GHS02 GHS07

Signal word Danger Hazard statements

Hazard statements
H224 Extremely flammable liquid and vapour.
H319 Causes serious eye irritation.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary statements

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

(Contd. on page 5)

(Contd. of page 4)

Product name: Ethyl vinyl ether

All components of this product are listed on the Canadian Domestic Substances List (DSL).

SARA Section 313 (specific toxic chemical listings) Substance is not listed.

California Proposition 65

Prop 65 - Chemicals known to cause cancer Substance is not listed.

Prop 65 - Developmental toxicity Substance is not listed.

Prop 65 - Developmental toxicity, female Substance is not listed.

Prop 65 - Developmental toxicity, male Substance is not listed.

Information about limitation of use: For use only by technically qualified individuals.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed. market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user. Conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Global Marketing Department
Date of preparation / last revision 03/03/2017 / Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
HMIS: Hazardous Materials Information System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
LC50: Lethal doncentration, 50 percent
LD50: Lethal doncentration, 50 percent
LD50: Lethal doncentration of Governmental Industrial Hygienists (USA)
OSHA: Occupational Safety and Health Administration (USA)
NTP: National Toxicology Program (USA)
IARC: International Agency for Research on Cancer
EPA: Environmental Protection Agency (USA)
Flam. Liq. 1: Flammable liquids, Hazard Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 3
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3