

SAFETY DATA SHEET

Version 5.8
Revision Date 06/02/2016
Print Date 11/10/2018

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : 1,4-Dioxane

Product Number : 34857
Brand : Sigma-Aldrich
Index-No. : 603-024-00-5

CAS-No. : 123-91-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832
Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Eye irritation (Category 2A), H319

Carcinogenicity (Category 2), H351

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word : Danger

Hazard statement(s)

H225

H319

H335

H351

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause respiratory irritation.

Suspected of causing cancer.

Precautionary statement(s)

P201

P202

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

P210

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

| | |
|--------------------|--|
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ ventilating/ lighting/ equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P261 | Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. |
| P264 | Wash skin thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/ protective clothing/ eye protection/ face protection. |
| P303 + P361 + P353 | IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. |
| P304 + P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308 + P313 | IF exposed or concerned: Get medical advice/ attention. |
| P337 + P313 | If eye irritation persists: Get medical advice/ attention. |
| P370 + P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. |
| P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/ container to an approved waste disposal plant. |

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

May form explosive peroxides., Repeated exposure may cause skin dryness or cracking.
May form explosive peroxides.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

| | | |
|---------------------|---|--|
| Synonyms | : | Dioxane Diethylene oxide |
| Formula | : | C ₄ H ₈ O ₂ |
| Molecular weight | : | 88.11 g/mol |
| CAS-No. | : | 123-91-1 |
| EC-No. | : | 204-661-8 |
| Index-No. | : | 603-024-00-5 |
| Registration number | : | 01-2119462837-26-XXXX |

Hazardous components

| Component | Classification | Concentration |
|--------------------|---|---------------|
| 1,4-Dioxane | | |
| | Flam. Liq. 2; Eye Irrit. 2A; Carc. 2; STOT SE 3; H225, H319, H335, H351 | <= 100 % |

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES**5.1 Extinguishing media****Suitable extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE**7.1 Precautions for safe handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****Components with workplace control parameters**

| Component | CAS-No. | Value | Control parameters | Basis |
|-------------|----------|--|------------------------------------|---|
| 1,4-Dioxane | 123-91-1 | TWA | 20.000000 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | Remarks | Liver damage Confirmed animal carcinogen with unknown relevance to humans Danger of cutaneous absorption | | |
| | | TWA | 20 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | | Liver damage Confirmed animal carcinogen with unknown relevance to humans Danger of cutaneous absorption | | |
| | | TWA | 25 ppm 90 mg/m3 | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 |
| | | Skin notation | | |
| | | TWA | 100.000000 ppm 360.000000 mg/m3 | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| | | Skin designation The value in mg/m3 is approximate. | | |
| | | TWA | 100 ppm 360 mg/m3 | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| | | Skin designation The value in mg/m3 is approximate. | | |
| | | C | 1.000000 ppm 3.600000 mg/m3 | USA. NIOSH Recommended Exposure Limits |
| | | Potential Occupational Carcinogen See Appendix A 30 minute ceiling value | | |
| | | PEL | 0.28 ppm 1 mg/m3 | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| | | Skin | | |

Derived No Effect Level (DNEL)

| Application Area | Exposure routes | Health effect | Value |
|------------------|-----------------|----------------------------|-----------|
| Workers | Inhalation | Long-term local effects | 144 mg/m3 |
| Workers | Inhalation | Long-term systemic effects | 73 mg/m3 |
| Workers | Skin contact | Long-term systemic effects | 21 mg/m3 |

Predicted No Effect Concentration (PNEC)

| Compartment | Value |
|------------------------------|-------------|
| Soil | 0.153 mg/kg |
| Marine water | 0.67 mg/l |
| Fresh water | 10 mg/l |
| Fresh water sediment | 37 mg/kg |
| Sewage treatment plant | 2700 mg/l |
| Aquatic intermittent release | 10 mg/l |

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: > 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Chloroprene

Minimum layer thickness: 0.6 mm

Break through time: 35 min

Material tested:Camapren® (KCL 722 / Aldrich Z677493, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- | | |
|--|---|
| a) Appearance | Form: liquid Colour: colourless |
| b) Odour | No data available |
| c) Odour Threshold | No data available |
| d) pH | 6.0 - 8 at 500 g/l at 20 °C (68 °F) |
| e) Melting point/freezing point | Melting point/range: 10 - 12 °C (50 - 54 °F) - lit. |
| f) Initial boiling point and boiling range | 100 - 102 °C (212 - 216 °F) - lit. |
| g) Flash point | 12 °C (54 °F) - closed cup |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | No data available |

| | |
|---|--|
| j) Upper/lower flammability or explosive limits | Upper explosion limit: 22 %(V) Lower explosion limit: 2 %(V) |
| k) Vapour pressure | 36 hPa (27 mmHg) at 20 °C (68 °F) 53 hPa (40 mmHg) at 25.20 °C (77.36 °F) |
| l) Vapour density | 3.04 - (Air = 1.0) |
| m) Relative density | 1.034 g/cm ³ at 25 °C (77 °F) |
| n) Water solubility | completely miscible |
| o) Partition coefficient: n-octanol/water | log Pow: -0.27 |
| p) Auto-ignition temperature | 375 °C (707 °F) |
| q) Decomposition temperature | No data available |
| r) Viscosity | No data available |
| s) Explosive properties | No data available |
| t) Oxidizing properties | No data available |

9.2 Other safety information

| | |
|-------------------------|----------------------------|
| Surface tension | 36.9 mN/m at 25 °C (77 °F) |
| Relative vapour density | 3.04 - (Air = 1.0) |

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

Contains the following stabiliser(s):

BHT (1.4 ppm)

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Oxygen, Oxidizing agents, Halogens, Reducing agents, Perchlorates., Trimethylaluminum

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 4,200 mg/kg

LC50 Inhalation - Rat - 2 h - 46,000 mg/m³

Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and Taste):Eye:Other.

LD50 Dermal - Rabbit - 7,858 mg/kg

No data available

Skin corrosion/irritation

Skin - Human

Remarks: Chronic exposure causes drying effect on the skin and eczema.

Skin - Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation - 24 h

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

Laboratory experiments have shown mutagenic effects.

Carcinogenicity

This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

Limited evidence of carcinogenicity in animal studies

IARC: 2B - Group 2B: Possibly carcinogenic to humans (1,4-Dioxane)

NTP: Reasonably anticipated to be a human carcinogen (1,4-Dioxane)

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: JG8225000

Nausea, Vomiting, Weakness, Dizziness, Vertigo, Headache, Sweating, loss of appetite, Kidney injury may occur., Liver injury may occur.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Liver - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION**12.1 Toxicity**

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 985 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates EC50 - Daphnia magna (Water flea) - 8,450 mg/l - 24 h

Toxicity to algae EC50 - Desmodesmus subspicatus (green algae) - > 500 mg/l - 72 h

12.2 Persistence and degradability

Biodegradability Result: < 5 % - Not readily biodegradable.

12.3 Bioaccumulative potential

Does not bioaccumulate.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

No data available

13. DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods****Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION**DOT (US)**

UN number: 1165 Class: 3
Proper shipping name: Dioxane
Reportable Quantity (RQ): 100 lbs

Packing group: II

Poison Inhalation Hazard: No

IMDG

UN number: 1165 Class: 3
Proper shipping name: DIOXANE

Packing group: II

EMS-No: F-E, S-D

IATA

UN number: 1165 Class: 3
Proper shipping name: Dioxane

Packing group: II

15. REGULATORY INFORMATION**SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

| | CAS-No. | Revision Date |
|-------------|----------|---------------|
| 1,4-Dioxane | 123-91-1 | 2007-07-01 |

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

| | CAS-No. | Revision Date |
|-------------|----------|---------------|
| 1,4-Dioxane | 123-91-1 | 2007-07-01 |

Pennsylvania Right To Know Components

| | CAS-No. | Revision Date |
|-------------|----------|---------------|
| 1,4-Dioxane | 123-91-1 | 2007-07-01 |

New Jersey Right To Know Components

| | CAS-No. | Revision Date |
|-------------|----------|---------------|
| 1,4-Dioxane | 123-91-1 | 2007-07-01 |

California Prop. 65 Components

WARNING! This product contains a chemical known to the State of California to cause cancer.

1,4-Dioxane

CAS-No.
123-91-1

Revision Date
2007-09-28

16. OTHER INFORMATION**Full text of H-Statements referred to under sections 2 and 3.**

| | |
|------------|--|
| Carc. | Carcinogenicity |
| Eye Irrit. | Eye irritation |
| Flam. Liq. | Flammable liquids |
| H225 | Highly flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H351 | Suspected of causing cancer. |
| STOT SE | Specific target organ toxicity - single exposure |

HMIS Rating

| | |
|------------------------|---|
| Health hazard: | 2 |
| Chronic Health Hazard: | * |
| Flammability: | 3 |
| Physical Hazard | 0 |

NFPA Rating

| | |
|--------------------|---|
| Health hazard: | 2 |
| Fire Hazard: | 3 |
| Reactivity Hazard: | 0 |

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation
Product Safety – Americas Region
1-800-521-8956

Version: 5.8

Revision Date: 06/02/2016

Print Date: 11/10/2018