

Safety Data Sheet 8768107

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 06/15/2018 Version: 1.0

# **SECTION 1: Identification**

#### Identification

Product form : Substance

Substance name 2-Methoxybenzyl isothiocyanate

CAS No 17608-09-2 Product code 8768-1-07 Formula : C9H9NOS Other means of identification : MFCD00041111

#### Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

## Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

# **Emergency telephone number**

Emergency number : (844) 523-4086 (3E Company - Account 10069)

# SECTION 2: Hazard(s) identification

#### Classification of the substance or mixture

#### Classification (GHS-US)

Acute Tox. 4 (Oral) H302 - Harmful if swallowed Acute Tox. 4 (Dermal) H312 - Harmful in contact with skin

Acute Tox. 4 (Inhalation:dust,mist) H332 - Harmful if inhaled

Skin Corr. 1B H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage Eye Dam. 1 Skin Sens. 1 H317 - May cause an allergic skin reaction STOT SE 3 H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

### Label elements

## **GHS-US** labeling

Hazard pictograms (GHS-US)





GHS05

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

H314 - Causes severe skin burns and eve damage

H317 - May cause an allergic skin reaction H335 - May cause respiratory irritation

Precautionary statements (GHS-US) P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P264 - Wash skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P272 - Contaminated work clothing must not be allowed out of the workplace P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301+P312 - If swallowed: Call a POISON CENTER or doctor/ physician if you feel unwell

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

06/15/2018 SDS ID: 8768107 EN (English US) Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

 ${\it P305+P351+P338-If in eyes: Rinse\ cautiously\ with\ water\ for\ several\ minutes.\ Remove\ contact}$ 

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P330 - Rinse mouth

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P363 - Wash contaminated clothing before reuse

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/container to an approved waste disposal plant

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

# **SECTION 3: Composition/information on ingredients**

# 3.1. Substance

Substance type : Mono-constituent

| Name  | Product identifier  | %      | Classification (GHS-US)  |
|---|---------------------|--------|--|
| 2-Methoxybenzyl isothiocyanate (Main constituent) | (CAS No) 17608-09-2 | <= 100 | Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation:dust,mist),<br>H332<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>STOT SE 3, H335 |

Full text of H-phrases: see section 16

#### 3.2. Mixture

Not applicable

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

 $respiration. \ Get \ immediate \ medical \ advice/attention.$ 

First-aid measures after skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate

medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse

mouth out with water. Get immediate medical advice/attention.

# 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11.

Symptoms/injuries after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media

appropriate for surrounding fire.

# 5.2. Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides. Nitrogen oxides. Sulfur oxides.

# 5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area.

06/15/2018 EN (English US) SDS ID: 8768107 2/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting

Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe dust. Do not breathe gas, fumes, vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures

: Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

# 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment

Other information

: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up

: Minimize generation of dust. Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.

: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

#### 6.4. Reference to other sections

No additional information available

# SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed

Precautions for safe handling

: Handle empty containers with care because residual vapors are flammable.

: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures

: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

## 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations.

Storage conditions

: Keep container closed when not in use. Keep away from ignition sources. Moisture sensitive.

Keep contents under inert gas.

Incompatible materials

Refer to Section 10 on Incompatible Materials.

Storage area

: Store in dry, cool, well-ventilated area.

# SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

# 8.2. Exposure controls

Appropriate engineering controls

Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection

: Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection

: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection

Other information

: Safety shoes. 29 CFR 1910.136: Foot Protection.

06/15/2018 EN (English US) SDS ID: 8768107 3/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Low melting solid.
Color : No data available
Odor threshold : No data available
pH : No data available

Melting point : 28 °C

Freezing point : No data available Boiling point : 133 °C (@ 4 mm Hg) : No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) : No data available : No data available **Explosion limits** Explosive properties : No data available Oxidizing properties : No data available Vapor pressure : No data available Relative density : No data available Relative vapor density at 20 °C : No data available Molecular mass : 179.239 g/mol Solubility : No data available Log Pow : No data available : No data available Auto-ignition temperature Decomposition temperature No data available : No data available Viscosity Viscosity, kinematic : No data available Viscosity, dynamic : No data available

### 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

No additional information available

# 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

# 10.3. Possibility of hazardous reactions

No additional information available

## 10.4. Conditions to avoid

Keep away from heat, sparks and flame. Moisture.

# 10.5. Incompatible materials

Alcohols. Strong bases. Water. Amines. Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Dermal: Harmful in contact with skin. Inhalation:dust,mist: Harmful if

inhaled

06/15/2018 EN (English US) SDS ID: 8768107 4/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| 2-Methoxybenzyl isothiocyanate (17608-09-2)        |  |  |
|--|--|--|
| ATE US (oral)                                      | 500.000 mg/kg body weight                  |  |
| ATE US (dermal)                                    | 1100.000 mg/kg body weight                 |  |
| ATE US (dust, mist)                                | 1.500 mg/l/4h                              |  |
| Skin corrosion/irritation                          | : Causes severe skin burns and eye damage. |  |
| Serious eye damage/irritation                      | : Causes serious eye damage.               |  |
| Respiratory or skin sensitization                  | : May cause an allergic skin reaction.     |  |
| Germ cell mutagenicity                             | : Not classified                           |  |
| Carcinogenicity                                    | : Not classified                           |  |
| Reproductive toxicity                              | : Not classified                           |  |
| Specific target organ toxicity (single exposure)   | : May cause respiratory irritation.        |  |
| Specific target organ toxicity (repeated exposure) | : Not classified                           |  |
| Aspiration hazard                                  | : Not classified                           |  |

shortness of breath, headache, nausea.

Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

# **SECTION 12: Ecological information**

#### **Toxicity**

No additional information available

Symptoms/injuries after inhalation

# Persistence and degradability

No additional information available

#### **Bioaccumulative potential**

No additional information available

## **Mobility in soil**

No additional information available

# Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

# Waste treatment methods

: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber. Waste treatment methods Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

# **SECTION 14: Transport information**

# **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN2922 Corrosive liquids, toxic, n.o.s., 8, III


UN-No.(DOT) : UN2922

Proper Shipping Name (DOT) : Corrosive liquids, toxic, n.o.s.

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) 8 - Corrosive

6.1 - Poison



Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

06/15/2018 EN (English US) SDS ID: 8768107 5/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: 241 DOT Packaging Bulk (49 CFR 173.xxx)

**DOT Symbols** : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55

C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table

2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a **DOT Vessel Stowage Location** 

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

: 40 - Stow "clear of living quarters" **DOT Vessel Stowage Other** Other information : No supplementary information available.

**TDG** 

No additional information available

Transport by sea

UN-No. (IMDG) : 2922

Proper Shipping Name (IMDG) : CORROSIVE LIQUID, TOXIC, N.O.S.

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : III - substances presenting low danger

Air transport

UN-No. (IATA) : 2922

Proper Shipping Name (IATA) Corrosive liquid, toxic, n.o.s.

Class (IATA) : 8 - Corrosives Packing group (IATA) : III - Minor Danger

# **SECTION 15: Regulatory information**

# 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

2-Methoxybenzyl isothiocyanate CAS No 17608-09-2 100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

## 15.2. International regulations

No additional information available

### **EU-Regulations**

No additional information available

#### National regulations

No additional information available

06/15/2018 EN (English US) SDS ID: 8768107 6/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

# **SECTION 16: Other information**

#### Full text of H-phrases:

| Acute Tox. 4 (Dermal)               | Acute toxicity (dermal) Category 4                          |  |
|-------------------------------------|---|--|
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4            |  |
| Acute Tox. 4 (Oral)                 | Acute toxicity (oral) Category 4                            |  |
| Eye Dam. 1                          | Serious eye damage/eye irritation Category 1                |  |
| Skin Corr. 1B                       | Skin corrosion/irritation Category 1B                       |  |
| Skin Sens. 1                        | Skin sensitization Category 1                               |  |
| STOT SE 3                           | Specific target organ toxicity (single exposure) Category 3 |  |
| H302                                | Harmful if swallowed  |  |
| H312                                | Harmful in contact with skin                                |  |
| H314                                | Causes severe skin burns and eye damage                     |  |
| H317                                | May cause an allergic skin reaction                         |  |
| H318                                | Causes serious eye damage                                   |  |
| H332                                | Harmful if inhaled  |  |
| H335                                | May cause respiratory irritation                            |  |
|                                     |   |  |

NFPA health hazard

: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was

iiven.

NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



**HMIS III Rating** 

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

06/15/2018 EN (English US) SDS ID: 8768107 7/7