



EREZTECH LLC

11555 Medlock Bridge Road, Suite 100, Johns Creek, GA 30097, USA

T: +1.888.658.1221 F: 1.678.619.2020

E: info@ereztech.com W: <http://ereztech.com>

SAFETY DATA SHEET

Section 1. Identification

Product Name: Bis(t-butylamino)silane
Product Type: Liquid
CAS Number: 186598-40-3
Product Number: SI8403
Product Manufacturer: Ereztech LLC
11555 Medlock Bridge Road, Suite 100
Johns Creek, GA 30097
Product Information: (888) 658-1221
In case of an emergency: (888) 658-1221 (for spill, leak, fire or exposure)
*** Contact manufacturer for all non-emergency calls.

Section 2. Hazards Identification

Hazards Identification

Classification: FLAMMABLE LIQUIDS; - Category 3, H226
SUBSTANCE AND MIXTURES, WHICH IN CONTACT WITH WATER,
EMIT FLAMMABLE GASES; - Category 1, H260
ACUTE TOXICITY, ORAL; - Category 3, H301
SKIN CORROSION/IRRITATION; - Category 1B, H314
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1, H318
ACUTE TOXICITY, INHALATION; - Category 4, H332
HAZARDOUS TO THE AQUATIC ENVIRONMENT, ACUTE TOXICITY;
- Category 3, H402
HAZARDOUS TO THE AQUATIC ENVIRONMENT, CHRONIC
TOXICITY; - Category 3, H412

GHS label elements

Hazard pictograms:



Signal word: DANGER

Bis(t-butylamino)silane

Safety Data Sheet

Section 2. Hazards Identification

Hazard statements:

H226: Flammable liquid and vapor.
H260: In contact with water releases flammable gases which may ignite spontaneously.
H301: Toxic if swallowed.
H314: Causes severe skin burns and eye damage.
H318: Causes serious eye damage.
H332: Harmful if inhaled.
H402: Harmful to aquatic life.
H412: Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P223: Keep away from any possible contact with water, because of violent reaction and possible flash fire.
P231 + P232: Handle under inert gas. Protect from moisture.
P233: Keep container tightly closed.
P240: Ground/Bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting/handling equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P261: Avoid breathing fumes, gases, mists, vapors and sprays.
P264: Wash skin thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301 + P330 + P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor/physician.
P330: Rinse mouth.

Bis(t-butylamino)silane

Safety Data Sheet

Section 2. Hazards Identification

Response (cont.):	P334 + P335: Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages. P363: Wash contaminated clothing before reuse. P370 + P378: In case of fire: Use alcohol-resistant foam, dry chemical or carbon dioxide for extinction. DO NOT USE WATER. P391: Collect spillage.
Storage:	P402 + P404: Store in a dry place. Store in a closed container. P403 + P235: Store in a well ventilated place. Keep cool. P405: Store locked up. P422: Store under inert gas.
Disposal:	P501: Dispose of contents/ container to an approved wasted disposal plant.
OSHA/HCS status:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Hazards not otherwise classified:	Reacts violently with water to release a flammable gas which may ignite spontaneously.

Section 3. Composition/Information on Ingredients

Substances

Formula	: C ₈ H ₂₂ N ₂ Si
Molecular weight	: 174.36 g/mol
CAS-No.	: 186598-40-3

Ingredient Name	%	CAS Number
Bis(t-butylamino)silane	>95	186598-40-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First Aid Measures

Description of Necessary First Aid Measures

General Advice:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue rinsing for a minimum of 15 minutes. Get immediate medical attention.
Skin Contact:	Take off contaminated clothing and shoes immediately. Wash off contaminated skin with soap and plenty of water. Get immediate medical attention.

Bis(t-butylamino)silane

Safety Data Sheet

Section 4. First Aid Measures

- Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Call a POISON CENTER or doctor/physician immediately.
- Ingestion:** Call a physician or POISON CONTROL CENTER immediately. Rinse mouth. Do NOT induce vomiting. Remove dentures if any. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most Important Symptoms/Effects, Acute And Delayed Potential Acute Health Effects

- Eye Contact:** Severe chemical and thermal burns to the eye may be expected and may cause permanent eye damage.
- Inhalation:** Due to the products violent reactivity with water, inhalation of product may be expected to cause chemical and thermal burns of mucous membranes. Symptoms may include a burning sensation, difficulty in breathing, coughing, wheezing, headache, nausea and vomiting. Inhalation may be fatal as a result of spasm, inflammation, swelling of the throat, chemical pneumonitis and pulmonary edema.
- Skin Contact:** Skin contact with this product may be expected to cause severe chemical burns.
- Ingestion:** Ingestion will result in burns of the mucous membranes of the mouth and throat and potential perforation of the esophagus and stomach.

Indication of Immediate Medical Attention and Special Treatment Needed, If Necessary

- Notes to Physician:** Treat symptomatically.
- Specific Treatments:** No specific treatment.
- Protection of First Responders:** No action taken shall be taken involving any personal risk without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire Fighting Measures

- Suitable Extinguishing Media:** THE MOST EFFECTIVE FIRE EXTINGUISHING AGENT IS DRY CHEMICAL POWDER PRESSURIZED WITH NITROGEN. Vermiculite, sand, dry chemical or carbon dioxide (CO₂) may also be used. CAUTION: PRODUCT MAY REIGNITE.

Bis(t-butylamino)silane

Safety Data Sheet

Section 5. Fire Fighting Measures

Unsuitable Extinguishing Media:

Do not use water (fog, spray or jet).

Fire and Explosion Hazards:

Flammable liquid. This material reacts with water to produce tert-butylamine, which is highly flammable and highly toxic. Vapors may collect in low places to present an explosion hazard and may travel over distance to a source of ignition and flashback. Do not cut, grind, drill or weld on or near the container (even empty) of this product because an explosion may result. Keep away from heat, sparks and flame.

Product of Combustion:

When exposed to fire, decomposition products which may include toxic and irritating organic acid vapors, tert-butylamine, ammonia, carbon oxides (CO_x), nitrogen oxides and silicon oxides.

Protection of Firefighters:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Fire-fighters should wear appropriate protection equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6. Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures**For Non-emergency Personnel:**

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid inhalation of dusts or mist. Provide adequate ventilation. Wear respiratory protection. Put on appropriate personal protective equipment.

For Emergency Responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental Precautions:

Do not allow dispersal of spilled material and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Bis(t-butylamino)silane

Safety Data Sheet

Section 6. Accidental Release Measures

Methods for Containment

Small/Large Spill:

Spilled material will likely give off smoke and fumes. Ignition may occur immediately. Keep away from ignition sources. Contain and collect spillage with non-combustible, dry absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in dry container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Do not flush spill area with water or aqueous cleaning solution.

Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and Storage

Precautions:

Avoid contact with skin, eyes and clothing. Avoid inhalation of aerosols, gases, vapors or mist. Do not ingest. Provide adequate ventilation. Keep away from sources of ignition – No smoking.

Protective Measures:

Protect against electrostatic charges. Use explosion-proof electrical/ventilating/lighting/handling equipment. Use only non-sparking tools and equipment. Put on appropriate personal protective equipment (see Section 8). Keep in the original container kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

General Occupational Hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Safe Storage Conditions:

Store under an inert gas. Nitrogen with less than 5 ppm each of moisture and oxygen is recommended. Keep away from air, moisture, heat, sparks and open flames. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials noted above and food and drink. Keep container tightly closed and sealed until ready for use. Store locked up.

Bis(t-butylamino)silane

Safety Data Sheet

Section 8. Exposure Controls/Personal Protection

Introductory Remarks:

These recommendations provide general guidance for handling this product. Because work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and conduct regular repairs. Waste from these procedures should be handled in accordance with Section 13.

Occupational Exposure Limits:

Product contains no substances with occupational exposure limit values.

Engineering Controls:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute. Provide an eyewash/shower station.

Environmental Exposure Controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual Protection Measures**Hygiene Measures:**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Remove all soiled and contaminated clothing immediately. Do not inhale dusts or mists. Avoid contact with eyes and skin. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles, faceshield (8-inch minimum). Refer to 29 CFR 1910.133, ANSI Z87.1, or European Standard EN166.

Skin Protection**Hand Protection:**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties.

Bis(t-butylamino)silane

Safety Data Sheet

Section 8. Exposure Controls/Personal Protection

Hand Protection (cont.):

It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Chemical-resistant gloves.

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. For full contact, use Neoprene or nitrile rubber.

Other Skin Protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Section 9. Physical and Chemical Properties

Physical State:	Liquid.
Color:	Clear.
Odor:	Amine-like.
Odor Threshold:	No data available.
pH:	No data available.
Melting Point:	<-40 °C (-40 °F).
Boiling Point:	167 °C (332.6 °F).
Flash Point:	30 °C (86 °F).
Auto-ignition temperature:	190.0 °C (374 °F).
Specific Gravity:	0.816 g/ml.
Vapor Pressure:	1.15 Torr @ 20 °C.
Vapor Density:	>1.

Bis(t-butylamino)silane

Safety Data Sheet

Section 9. Physical and Chemical Properties

Water Solubility:	Reacts violently, may ignite upon exposure.
Evaporation Rate:	No data available.
Viscosity:	No data available.
Volatile %:	No data available.
VOC Content:	No data available.

VOCs are calculated following the requirements under 40 CFR, Part 59, Subpart C for Consumer Products and Subpart D for Architectural Coatings.

Section 10. Stability and Reactivity

Reactivity:	This product reacts violently with water to produce tert-butylamine, a highly flammable and toxic gas.
Chemical Stability:	This product is stable when stored under a dry, inert atmosphere and away from heat. Nitrogen containing less than 5 ppm each moisture and air is recommended. This product is not sensitive to impact.
Conditions to Avoid:	Keep away from moisture, heat and sources of ignition.
Incompatible Materials:	Water, oxidizing agents and compounds containing active hydrogen such as alcohols and acids.
Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products formed under fire conditions: toxic and irritating organic acid vapors and tert-butylamine. In the event of a fire: see section 5.
Possibility of Hazardous Reactions:	This product reacts violently with water to produce tert-butylamine, a highly flammable and toxic gas.

Section 11. Toxicological Information

Information on Toxicological Effects

Acute Toxicity	: LD50 oral rat: 200-500 mg/kg.
Irritation/Corrosion	: No specific data available. May be expected to cause severe thermal and/or chemical burns to the skin, eyes and exposed mucous membranes.
Sensitization	: No specific data available.
Germ Cell Mutagenicity	: No effects known.
Carcinogenicity	
IARC	: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Bis(t-butylamino)silane

Safety Data Sheet

Section 11. Toxicological Information

ACGIH	: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH.
NTP	: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.
OSHA	: No component of this product present at levels greater than 0.1% is identified as probable, possible or confirmed human carcinogen by OSHA.
Reproductive Toxicity	: This product is not expected to cause reproductive or developmental effects.
Teratogenicity	: No specific data available.
Specific Target Organ Toxicity (single exposure)	: Respiratory tract irritation/damage through thermal and chemical burns.
Specific Target Organ Toxicity (repeated exposure)	: No specific data available.
Aspiration Hazard	: No specific data available.
Information on the likely routes of exposure	: Harmful by inhalation, ingestion and skin/eye exposure.
Additional Information	: None

Section 12. Ecological Information

Numerical Measures of Toxicity

Toxicity to Fish	: No specific data available.
Toxicity to daphnia and other aquatic invertebrates	: No specific data available.
Toxicity to algae	: No specific data available.
Persistence and Degradability	
Biodegradability	: No specific data available.
Bioaccumulative potential	: No specific data available.
Mobility in soil	: No specific data available.
Other Adverse Effects	: Product rapidly decomposes to t-butylamine upon exposure to water. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Bis(t-butylamino)silane

Safety Data Sheet

Section 13. Disposal Considerations

Waste Treatment Methods

Product

Dispose of in accordance with local, state, and federal regulations. Refer to 40 CFR 260-299 for complete waste disposal regulations. Consult your local, state, or federal agency before disposing of any chemicals.

Contaminated packaging

Empty containers retain product residue (solids and/or dust) and can be dangerous. DO NOT EXPOSE SUCH CONTAINERS TO AIR, MOISTURE, HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Section 14. Transport Information

	DOT	IMDG	IATA
UN Number	UN 2924	UN 2924	UN 2924
UN Proper Shipping Name	Flammable liquid, corrosive n.o.s. (Bis(tert-butylamino) silane)	FLAMMABLE LIQUID, CORROSIVE N.O.S. (Bis(tert-butylamino) silane)	Flammable liquid, corrosive n.o.s. (Bis(tert-butylamino) silane)
Transport Hazard Classes	3 (8)	3 (8)	3 (8)
Packing Group	II	II	II
Environmental Hazards	Yes	Yes	Yes
Additional Information	-	EMS-No: F-E, S-C	-

Special Precautions for User

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transporting in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

Section 15. Regulatory Information

TSCA (Toxic Substance Control Act):

This product is not listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory). Use of this product is restricted to research and development only. This product must be used under the supervision of a technically qualified individual as defined by the TSCA. This product must not be used for commercial purposes or in formulations for commercial purposes.

Bis(t-butylamino)silane

Safety Data Sheet

Section 15. Regulatory Information

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Reactivity Hazard, Acute Health Hazard.

Massachusetts Right to Know Components

No components are subject to Massachusetts Right to Know Act.

Pennsylvania Right to Know Components

No components are subject to Pennsylvania Right to Know Act.

New Jersey Right to Know Components

No components are subject to New Jersey Right to Know Act.

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Section 16. Other Information

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Bis(t-butylamino)silane

Safety Data Sheet

Section 16. Other Information

HMIS Rating

HEALTH	4
FLAMMABILITY	3
PHYSICAL HAZARD	2

History

Date of printing : 9/21/18

Date of issue/Date of Revision : 9/21/18

Date of previous issue : None

References : None available

Abbreviations and Acronyms

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DOT: US Department of Transportation

GHS: Globally Harmonized System of Classification and Labeling of Chemicals

HMIS: Hazardous Materials Identification System

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

IMDG: International Maritime Code for Dangerous Goods

NFPA: National Fire Protection Association

NIOSH: National Institute of Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

SARA: Superfund Amendments and Reauthorization Act

VOC: Volatile Organic Compound

Disclaimer

The information herein is believed to be accurate and is presented in good faith; however, no warranties or representations are made by Ereztech LLC regarding the accuracy or completeness of the information. Ereztech LLC shall not be liable for any damages resulting from the handling, or from the contact with the above product.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.