

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 07/20/2009

Reviewed on 07/17/2009

1 Identification of substance:

Product details:

Product name: Acetone-d6

Stock number:

16797
42262

Manufacturer/Supplier:

Alfa Aesar, A Johnson Matthey Company
Johnson Matthey Catalog Company, Inc.
30 Bond Street
Ward Hill, MA 01835-8099
Emergency Phone: (978) 521-6300
CHEMTREC: (800) 424-9300
Web Site: www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency information:

During normal hours the Health, Safety and Environmental Department. After normal hours call Chemtrec at (800) 424-9300.

2 Composition/Data on components:

Chemical characterization:

Description: (CAS#)


Acetone-d6 (CAS# 666-52-4): 100%

Identification number(s):

EINECS Number: 211-563-9

3 Hazards identification

Hazard description:



Xi Irritant
F Highly flammable

Information pertaining to particular dangers for man and environment

R 11 Highly flammable.

R 36 Irritating to eyes.

R 66 Repeated exposure may cause skin dryness or cracking

R 67 Vapours may cause drowsiness and dizziness

Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH	1
FIRE	3
REACTIVITY	1

Health (acute effects) = 1

Flammability = 3

Reactivity = 1

GHS label elements



Danger

2.6/2 - Highly flammable liquid and vapour.



Warning

3.3/2A - Causes serious eye irritation.

3.8/3 - May cause drowsiness or dizziness.

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

USA

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 07/20/2009

Reviewed on 07/17/2009

Product name: Acetone-d6

(Contd. of page 1)

Response:

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER or doctor/physician if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

4 First aid measures**After inhalation**

Supply fresh air. If required, provide artificial respiration. Keep patient warm.

Seek immediate medical advice.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Seek immediate medical advice.

After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing Seek immediate medical advice.

5 Fire fighting measures**Suitable extinguishing agents**

Carbon dioxide, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards caused by the material, its products of combustion or resulting gases:

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

6 Accidental release measures**Person-related safety precautions:**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Measures for environmental protection:

Dilute with plenty of water.

Do not allow material to be released to the environment without proper governmental permits.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Keep away from ignition sources.

Additional information:

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage**Handling****Information for safe handling:**

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Information about protection against explosions and fires:

Keep ignition sources away.

Protect against electrostatic charges.

(Contd. on page 3)

-USA-

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 07/20/2009

Reviewed on 07/17/2009

Product name: Acetone-d6

(Contd. of page 2)

Fumes can combine with air to form an explosive mixture.

Storage

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Store away from oxidizing agents.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

8 Exposure controls and personal protection

Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Components with limit values that require monitoring at the workplace:

Acetone

ppm

ACGIH TLV	500; 750-STEL
	Not classified as a human carcinogen
Austria MAK	750
Belgium TWA	750; 1000-STEL
Denmark TWA	250
Finland TWA	500; 625-STEL
France VME	750
Germany MAK	500
Hungary TWA	600 mg/m3; 1200 mg/m3-STEL
Japan OEL	200
Korea TLV	500; 750-STEL
Netherlands MAC-TGG	750
Norway TWA	125
Poland TWA	600 mg/m3; 1800 mg/m3-STEL
Russia TWA	200; 200-STEL
Sweden NGV	250; 500-KTV
Switzerland MAK-W	500; 1000-STEL
United Kingdom TWA	750; 1500-STEL
USA PEL	1000

Additional information: No data

Personal protective equipment**General protective and hygienic measures**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.

Use suitable respirator when high concentrations are present.

Protection of hands: Impervious gloves

Eye protection: Safety glasses

Body protection: Protective work clothing.

9 Physical and chemical properties:

General Information

Form:	Liquid
Color:	Colorless
Odor:	Acetone-like

Change in condition

Melting point/Melting range:	-94°C (-137°F)
Boiling point/Boiling range:	55.5°C (132°F)
Sublimation temperature / start:	Not determined

Flash point: -17°C (1°F)

Ignition temperature: 465°C (869°F)

Decomposition temperature: Not determined

Explosion limits:

Lower: 2.12 Vol %

(Contd. on page 4)

- USA -

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 07/20/2009

Reviewed on 07/17/2009

Product name: Acetone-d6

(Contd. of page 3)

Upper:	13.2 Vol %
Vapor pressure:	Not determined
Density at 20°C (68°F):	0.872 g/cm ³
Solubility in / Miscibility with Water:	Fully miscible
Viscosity: dynamic at 20°C (68°F):	0.32 mPas

10 Stability and reactivity

Thermal decomposition / conditions to be avoided:

Decomposition will not occur if used and stored according to specifications.

Materials to be avoided: Oxidizing agents

Dangerous reactions Reacts violently with nitric acid (HNO₃).

Dangerous products of decomposition: Carbon monoxide and carbon dioxide

11 Toxicological information

Acute toxicity:

Primary irritant effect:

on the skin: Causes mild irritant effect.

on the eye: Irritating effect.

Sensitization: No sensitizing effects known.

Subacute to chronic toxicity:

Acetone may cause narcosis in high concentration. It acts to dry and defat skin, causing irritation. Inhalation may cause headache and dizziness as well as irritation of the respiratory tract. Chronic exposure may cause liver and kidney injury.

Additional toxicological information:

To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.

12 Ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Do not allow material to be released to the environment without proper governmental permits.

13 Disposal considerations

Product:

Recommendation Consult state, local or national regulations to ensure proper disposal.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

DOT regulations:



Hazard class:

3

Identification number:

UN1090

Packing group:

II

Hazardous substance:

5000 lbs, 2270 kg

Proper shipping name (technical name): ACETONE

(Contd. on page 5)

-USA-

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 07/20/2009

Reviewed on 07/17/2009

Product name: Acetone-d6

(Contd. of page 4)

Label 3

Land transport ADR/RID (cross-border)



ADR/RID class: 3 (F1) Flammable liquids
 Danger code (Kemler): 33
 UN-Number: 1090
 Packaging group: II
 Description of goods: 1090 ACETONE

Maritime transport IMDG:



IMDG Class: 3
 UN Number: 1090
 Label: 3
 Packaging group: II
 EMS Number: F-E, S-D
 Marine pollutant: No
 Proper shipping name: ACETONE

Air transport ICAO-TI and IATA-DGR:



ICAO/IATA Class: 3
 UN/ID Number: 1090
 Label: 3
 Packaging group: II
 Proper shipping name: ACETONE

UN "Model Regulation": UN1090, ACETONE, 3, II

15 Regulations

Product related hazard informations:

Hazard symbols:

Xi Irritant

F Highly flammable

Risk phrases:

11 Highly flammable.

36 Irritating to eyes.

66 Repeated exposure may cause skin dryness or cracking

67 Vapours may cause drowsiness and dizziness

Safety phrases:

9 Keep container in a well-ventilated place.

16 Keep away from sources of ignition - No smoking.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

National regulations

This product is not listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical Substance Inventory. Use of this product is restricted to research and development only.

Some or all of the components of this product are not listed on the Canadian Domestic Substances List (DSL) or the Canadian Non-Domestic Substances List (NDSL).

Information about limitation of use: For use only by technically qualified individuals.

16 Other information:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished

(Contd. on page 6)

USA

Material Safety Data Sheet

acc. to OSHA and ANSI

Printing date 07/20/2009

Reviewed on 07/17/2009

Product name: Acetone-d6

(Contd. of page 5)

without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing MSDS: Health, Safety and Environmental Department.

Contact: Zachariah Holt

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

- USA -