

1 Identification

Product identifier

Product name: 1-Butanol

Stock number: 22925

CAS Number:

71-36-3

EC number:

200-751-6

Index number:

603-004-00-6

Relevant identified uses of the substance or mixture and uses advised against.

Identified use: SU24 Scientific research and development

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Alfa Aesar
Thermo Fisher Scientific Chemicals, Inc.
30 Bond Street
Ward Hill, MA 01835-8099
Tel: 800-343-0660
Fax: 800-322-4757
Email: tech@alfa.com
www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency telephone number:

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

2 Hazard(s) identification

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Hazards not otherwise classified No information known.

Label elements

GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)

Hazard pictograms



GHS02 GHS05 GHS07

Signal word

Danger

Hazard statements

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.


P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

B2 - Flammable liquid

D2B - Toxic material causing other toxic effects



Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH 2 Health (acute effects) = 2

FIRE 3 Flammability = 3

REACTIVITY 1 Physical Hazard = 1

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Product name: 1-Butanol

(Contd. of page 1)

3 Composition/information on ingredients

Chemical characterization: Substances
CAS# Description:
71-36-3 1-Butanol
Concentration: ≤100%
Identification number(s):
EC number: 200-751-6
Index number: 603-004-00-6

4 First-aid measures

Description of first aid measures
After inhalation
Supply fresh air. If required, provide artificial respiration. Keep patient warm.
Seek immediate medical advice.
After skin contact
Immediately wash with water and soap and rinse thoroughly.
Seek immediate medical advice.
After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing Seek medical treatment.
Information for doctor
Most important symptoms and effects, both acute and delayed
Causes skin irritation.
Harmful if swallowed.
Causes serious eye damage.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media
Suitable extinguishing agents Carbon dioxide, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Special hazards arising from the substance or mixture
If this product is involved in a fire, the following can be released:
Carbon monoxide and carbon dioxide
Advice for firefighters
Protective equipment:
Wear self-contained respirator.
Wear fully protective impervious suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Environmental precautions: Do not allow product to reach sewage system or any water course.
Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to section 13.
Ensure adequate ventilation.
Prevention of secondary hazards: Keep away from ignition sources.
Reference to other sections
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
Protective Action Criteria for Chemicals
PAC-1: 60 ppm
PAC-2: 800 ppm
PAC-3: 8000** ppm

7 Handling and storage

Handling
Precautions for safe handling
Keep container tightly sealed.
Store in cool, dry place in tightly closed containers.
Ensure good ventilation at the workplace.
Information about protection against explosions and fires:
Protect against electrostatic charges.
Fumes can combine with air to form an explosive mixture.
Keep ignition sources away.
Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility: Store away from oxidizing agents.
Further information about storage conditions:
Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems:
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring at the workplace:

71-36-3 1-Butanol (100.0%)

PEL (USA) Long-term value: 300 mg/m³, 100 ppm

(Contd. on page 3)
USA

Product name: 1-Butanol

(Contd. of page 2)

REL (USA)	Ceiling limit value: 150 mg/m³, 50 ppm
TLV (USA)	Skin Long-term value: 61 mg/m³, 20 ppm
EL (Canada)	Long-term value: 15 ppm Ceiling limit value: 30 ppm
EV (Canada)	Long-term value: 20 ppm

Additional information: No data

Exposure controls

Personal protective equipment

General protective and hygienic measures
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Remove all soiled and contaminated clothing immediately.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Maintain an ergonomically appropriate working environment.

Breathing equipment: Use suitable respirator when high concentrations are present.

Recommended filter device for short term use:
Use a respirator with multi-purpose combination (US) or type ABEK (EN 14387) as a backup to engineering controls. Risk assessment should be performed to determine if air-purifying respirators are appropriate. Only use equipment tested and approved under appropriate government standards such as NIOSH (USA) or CEN (EU).

Protection of hands:
Impervious gloves
Check protective gloves prior to each use for their proper condition.
The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Material of gloves Nitrile rubber, NBR

Penetration time of glove material (in minutes) 480

Glove thickness: 0.4 mm

Eye protection:
Tightly sealed goggles
Safety glasses with side shields / NIOSH (US) or EN 166(EU)

Body protection: Protective work clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties	
General Information	
Appearance:	
Form:	Liquid
Odor:	Alcohol-like
Odor threshold:	Not determined.
pH-value (70 g/l) at 20 °C (68 °F): 7	
Change in condition	
Melting point/Melting range:	-90 °C (-130 °F)
Boiling point/Boiling range:	117-118 °C (243-244 °F)
Sublimation temperature / start:	Not determined
Flash point: 35 °C (95 °F)	
Flammability (solid, gaseous) Not determined.	
Ignition temperature: 340 °C (644 °F)	
Decomposition temperature: Not determined	
Auto igniting: Not determined.	
Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures is possible.	
Explosion limits:	
Lower:	1.5 Vol %
Upper:	9.4 Vol %
Vapor pressure at 20 °C (68 °F):	5.6 hPa (4 mm Hg)
Density at 20 °C (68 °F):	0.81 g/cm³ (6.759 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 20 °C (68 °F):	77 g/l
Partition coefficient (n-octanol/water): Not determined.	
Viscosity:	
dynamic at 20 °C (68 °F):	2.95 mPas
kinematic:	Not determined.
Other information No further relevant information available.	

10 Stability and reactivity

Reactivity No information known.

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions Reacts with strong oxidizing agents

Conditions to avoid No further relevant information available.

Incompatible materials: Oxidizing agents

Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

Information on toxicological effects	
Acute toxicity:	
Harmful if swallowed.	
The Registry of Toxic Effects of Chemical Substances (RTECS) contains acute toxicity data for this substance.	
LD/LC50 values that are relevant for classification:	
Oral	LD50 790 mg/kg (rat)
Skin irritation or corrosion: Causes skin irritation.	
Eye irritation or corrosion: Causes serious eye damage.	

(Contd. on page 4)
USA

Product name: 1-Butanol	
(Contd. of page 3)	
Sensitization: No sensitizing effects known.	
Germ cell mutagenicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains mutation data for this substance.	
Carcinogenicity: No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.	
Reproductive toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains reproductive data for this substance.	
Specific target organ system toxicity - repeated exposure: No effects known.	
Specific target organ system toxicity - single exposure: May cause drowsiness or dizziness. May cause respiratory irritation.	
Aspiration hazard: No effects known.	
Subacute to chronic toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains multiple dose toxicity data for this substance.	
Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.	

12 Ecological information	
Toxicity	
Aquatic toxicity: No further relevant information available.	
Persistence and degradability No further relevant information available.	
Bioaccumulative potential No further relevant information available.	
Mobility in soil No further relevant information available.	
Additional ecological information:	
General notes: Do not allow undiluted product or large quantities to reach ground water, water course or sewage system. Avoid transfer into the environment.	
Results of PBT and vPvB assessment	
PBT: Not applicable.	
vPvB: Not applicable.	
Other adverse effects No further relevant information available.	

13 Disposal considerations	
Waste treatment methods	
Recommendation Consult state, local or national regulations to ensure proper disposal.	
Uncleaned packagings:	
Recommendation: Disposal must be made according to official regulations.	

14 Transport information	
UN-Number DOT, IMDG, IATA	UN1120
UN proper shipping name DOT ADR IMDG, IATA	Butanols 1120 Butanols BUTANOLS
Transport hazard class(es) DOT  Class Label ADR	3 Flammable liquids 3
 Class Label IMDG, IATA	3 (F1) Flammable liquids 3
 Class Label	3 Flammable liquids 3
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids F-E,S-D A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.	
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L 5000 lbs, 2270 kg
Hazardous substance: Marine Pollutant (DOT):	No
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Product name: 1-Butanol

(Contd. of page 4)

UN "Model Regulation":

UN 1120 BUTANOLS, 3, III

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)
Hazard pictograms



GHS02 GHS05 GHS07

Signal word Danger

Hazard statements

H226 Flammable liquid and vapor.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.
All components of this product are listed on the Canadian Domestic Substances List (DSL).

SARA Section 313 (specific toxic chemical listings)

71-36-3 1-Butanol

California Proposition 65

Prop 65 - Chemicals known to cause cancer Substance is not listed.

Prop 65 - Developmental toxicity Substance is not listed.

Prop 65 - Developmental toxicity, female Substance is not listed.

Prop 65 - Developmental toxicity, male Substance is not listed.

Information about limitation of use: For use only by technically qualified individuals.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Global Marketing Department

Date of preparation/Revision: Print date, revision date and version number are in the header of each page.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

ACGIH: American Conference of Governmental Industrial Hygienists (USA)

OSHA: Occupational Safety and Health Administration (USA)

NTP: National Toxicology Program (USA)

IARC: International Agency for Research on Cancer

EPA: Environmental Protection Agency (USA)

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3