

## SAFETY DATA SHEET

Version 6.1  
Revision Date 07/25/2018  
Print Date 10/17/2019

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### 1.1 Product identifiers

Product name : Acrylonitrile-2-<SP>13</>C

Product Number : 586633

Brand : Aldrich

Index-No. : 608-003-00-4

CAS-No. : 89511-33-1

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

#### 1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.  
3050 Spruce Street  
ST. LOUIS MO 63103  
UNITED STATES

Telephone : +1 314 771-5765

Fax : +1 800 325-5052

#### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

##### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225

Acute toxicity, Oral (Category 3), H301

Acute toxicity, Inhalation (Category 3), H331

Acute toxicity, Dermal (Category 3), H311

Skin irritation (Category 2), H315

Serious eye damage (Category 1), H318

Skin sensitisation (Category 1), H317

Carcinogenicity (Category 1B), H350

Reproductive toxicity (Category 2), H361

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

Acute aquatic toxicity (Category 2), H401

Chronic aquatic toxicity (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapour.

H301 + H311 + H331

Toxic if swallowed, in contact with skin or if inhaled.

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

H318

Causes serious eye damage.

H335

May cause respiratory irritation.

H350

May cause cancer.

H361

Suspected of damaging fertility or the unborn child.

H411

Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P201

Obtain special instructions before use.

P202

Do not handle until all safety precautions have been read and understood.

P210

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233

Keep container tightly closed.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting equipment.

P242

Use only non-sparking tools.

P243

Take precautionary measures against static discharge.

P261

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264

Wash skin thoroughly after handling.

P270

Do not eat, drink or smoke when using this product.

P271

Use only outdoors or in a well-ventilated area.

P272

Contaminated work clothing should not be allowed out of the workplace.

P273

Avoid release to the environment.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P310 + P330

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P311

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor.

P305 + P351 + P338 + P310

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P308 + P313

IF exposed or concerned: Get medical advice/ attention.

P333 + P313

If skin irritation or rash occurs: Get medical advice/ attention.

P362

Take off contaminated clothing and wash before reuse.

P370 + P378

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391

Collect spillage.

P403 + P233

Store in a well-ventilated place. Keep container tightly closed.

P403 + P235

Store in a well-ventilated place. Keep cool.

P405

Store locked up.

P501

Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

Formula :  $^{13}\text{CC}_2\text{H}_3\text{N}$   
Molecular weight : 54.05 g/mol  
CAS-No. : 89511-33-1  
Index-No. : 608-003-00-4

#### Hazardous components

| Component                  | Classification   | Concentration |
|----------------------------|--|---------------|
| <b>Acrylonitrile-2-13C</b> |  |               |
|                            | Flam. Liq. 2; Acute Tox. 3;<br>Skin Irrit. 2; Eye Dam. 1; Skin<br>Sens. 1; Carc. 1B; Repr. 2;<br>STOT SE 3; Aquatic Acute 2;<br>Aquatic Chronic 2; H225,<br>H301 + H311 + H331, H315,<br>H317, H318, H335, H350,<br>H361, H411 | <= 100 %      |

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

##### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

##### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

##### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

##### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

##### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

### 5. FIREFIGHTING MEASURES

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

#### 5.2 Special hazards arising from the substance or mixture

Carbon oxides, Nitrogen oxides (NOx)

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

---

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
For personal protection see section 8.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

### 6.4 Reference to other sections

For disposal see section 13.

---

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.  
Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.  
For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store under inert gas. hygroscopic

Recommended storage temperature 2 - 8 °C

Storage class (TRGS 510): 3: Flammable liquids

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### Components with workplace control parameters

| Component           | CAS-No.    | Value  | Control parameters | Basis   |
|---------------------|------------|--|--------------------|---|
| Acrylonitrile-2-13C | 89511-33-1 | TWA  | 1.000000 ppm       | USA. NIOSH Recommended Exposure Limits            |
|                     | Remarks    | Potential Occupational Carcinogen<br>See Appendix A<br>Potential for dermal absorption<br>15 minute ceiling value                                |                    |   |
|                     |            | C  | 10.000000 ppm      | USA. NIOSH Recommended Exposure Limits            |
|                     |            | Potential Occupational Carcinogen<br>See Appendix A<br>Potential for dermal absorption<br>15 minute ceiling value                                |                    |   |
|                     |            | Substance listed; for more information see OSHA document 1910.1045   |                    |   |
|                     |            | PEL  | 2.000000 ppm       | OSHA Specifically Regulated Chemicals/Carcinogens |
|                     |            | 1910.1045<br>This section applies to all occupational exposures to acrylonitrile (AN), Chemical Abstracts Service Registry No. 000107131, except |                    |   |

|  |  |  |                    |   |
|--|--|--|--------------------|---|
|  |  | <p>as provided in paragraphs (a)(2) and (a)(3) of this section. This section does not apply to exposures which result solely from the processing, use, and handling of the following materials: (i) ABS resins, SAN resins, nitrile barrier resins, solid nitrile elastomers, and acrylic and modacrylic fibers, when these listed materials are in the form of finished polymers, and products fabricated from such finished polymers; (ii) Materials made from and/or containing AN for which objective data is reasonably relied upon to demonstrate that the material is not capable of releasing AN in airborne concentrations in excess of 1 ppm as an eight (8)-hour time-weighted average, under the expected conditions of processing, use, and handling which will cause the greatest possible release; and (iii) Solid materials made from and/or containing AN which will not be heated above 170 °F during handling, use, or processing Acrylonitrile or AN means acrylonitrile monomer, chemical formula <math>\text{CH}_2=\text{CHCN}</math><br/>         OSHA specifically regulated carcinogen</p>  |                    |   |
|  |  | STEL   | 10.000000 ppm      | OSHA Specifically Regulated Chemicals/Carcinogens                                       |
|  |  | <p>1910.1045<br/>         This section applies to all occupational exposures to acrylonitrile (AN), Chemical Abstracts Service Registry No. 000107131, except as provided in paragraphs (a)(2) and (a)(3) of this section. This section does not apply to exposures which result solely from the processing, use, and handling of the following materials: (i) ABS resins, SAN resins, nitrile barrier resins, solid nitrile elastomers, and acrylic and modacrylic fibers, when these listed materials are in the form of finished polymers, and products fabricated from such finished polymers; (ii) Materials made from and/or containing AN for which objective data is reasonably relied upon to demonstrate that the material is not capable of releasing AN in airborne concentrations in excess of 1 ppm as an eight (8)-hour time-weighted average, under the expected conditions of processing, use, and handling which will cause the greatest possible release; and (iii) Solid materials made from and/or containing AN which will not be heated above 170 °F during handling, use, or processing Acrylonitrile or AN means acrylonitrile monomer, chemical formula <math>\text{CH}_2=\text{CHCN}</math><br/>         OSHA specifically regulated carcinogen</p> |                    |   |
|  |  | PEL  | 2 ppm<br>4.5 mg/m3 | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
|  |  | <p>Skin<br/>         see Section 5213</p>  |                    |   |
|  |  | TWA  | 2 ppm              | USA. ACGIH Threshold Limit Values (TLV)   |
|  |  | <p>Central Nervous System impairment<br/>         Lower Respiratory Tract irritation<br/>         Confirmed animal carcinogen with unknown relevance to humans<br/>         Danger of cutaneous absorption</p>   |                    |   |
|  |  | TWA  | 1 ppm              | USA. NIOSH Recommended Exposure Limits  |
|  |  | <p>Potential Occupational Carcinogen<br/>         See Appendix A<br/>         Potential for dermal absorption</p>  |                    |   |
|  |  | C  | 10 ppm             | USA. NIOSH Recommended Exposure Limits  |
|  |  | <p>Potential Occupational Carcinogen<br/>         See Appendix A<br/>         Potential for dermal absorption</p>  |                    |   |

|  |  |  |        |   |
|--|--|--|--------|---|
|  |  | 15 minute ceiling value  |        |   |
|  |  | PEL  | 2 ppm  | OSHA Specifically Regulated Chemicals/Carcinogens |
|  |  | 1910.1045<br>This section applies to all occupational exposures to acrylonitrile (AN), Chemical Abstracts Service Registry No. 000107131, except as provided in paragraphs (a)(2) and (a)(3) of this section. This section does not apply to exposures which result solely from the processing, use, and handling of the following materials: (i) ABS resins, SAN resins, nitrile barrier resins, solid nitrile elastomers, and acrylic and modacrylic fibers, when these listed materials are in the form of finished polymers, and products fabricated from such finished polymers; (ii) Materials made from and/or containing AN for which objective data is reasonably relied upon to demonstrate that the material is not capable of releasing AN in airborne concentrations in excess of 1 ppm as an eight (8)-hour time-weighted average, under the expected conditions of processing, use, and handling which will cause the greatest possible release; and (iii) Solid materials made from and/or containing AN which will not be heated above 170 °F during handling, use, or processing Acrylonitrile or AN means acrylonitrile monomer, chemical formula CH <sub>2</sub> =CHCN<br>OSHA specifically regulated carcinogen |        |   |
|  |  | STEL   | 10 ppm | OSHA Specifically Regulated Chemicals/Carcinogens |
|  |  | 1910.1045<br>This section applies to all occupational exposures to acrylonitrile (AN), Chemical Abstracts Service Registry No. 000107131, except as provided in paragraphs (a)(2) and (a)(3) of this section. This section does not apply to exposures which result solely from the processing, use, and handling of the following materials: (i) ABS resins, SAN resins, nitrile barrier resins, solid nitrile elastomers, and acrylic and modacrylic fibers, when these listed materials are in the form of finished polymers, and products fabricated from such finished polymers; (ii) Materials made from and/or containing AN for which objective data is reasonably relied upon to demonstrate that the material is not capable of releasing AN in airborne concentrations in excess of 1 ppm as an eight (8)-hour time-weighted average, under the expected conditions of processing, use, and handling which will cause the greatest possible release; and (iii) Solid materials made from and/or containing AN which will not be heated above 170 °F during handling, use, or processing Acrylonitrile or AN means acrylonitrile monomer, chemical formula CH <sub>2</sub> =CHCN<br>OSHA specifically regulated carcinogen |        |   |
|  |  | Substance listed; for more information see OSHA document 1910.1045   |        |   |

## 8.2 Exposure controls

### Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

### Personal protective equipment

#### Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm  
Break through time: 480 min  
Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact  
Material: Chloroprene  
Minimum layer thickness: 0.6 mm  
Break through time: 30 min  
Material tested: Camapren® (KCL 722 / Aldrich Z677493, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

### **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### **Control of environmental exposure**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

---

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

### **9.1 Information on basic physical and chemical properties**

- |   |   |
|---|---|
| a) Appearance                                   | Form: clear, liquid   |
| b) Odour  | No data available   |
| c) Odour Threshold                              | No data available   |
| d) pH   | No data available   |
| e) Melting point/freezing point                 | Melting point/range: -83 °C (-117 °F) - lit.                          |
| f) Initial boiling point and boiling range      | 77 °C (171 °F) - lit.   |
| g) Flash point                                  | ca.-4.98 °C (23.04 °F) - closed cup                                   |
| h) Evaporation rate                             | No data available   |
| i) Flammability (solid, gas)                    | No data available   |
| j) Upper/lower flammability or explosive limits | Upper explosion limit: ca.17 %(V)<br>Lower explosion limit: ca.3 %(V) |
| k) Vapour pressure                              | ca.115 hPa at 20 °C (68 °F)   |
| l) Vapour density                               | No data available   |
| m) Relative density                             | 0.83 g/cm <sup>3</sup> at 25 °C (77 °F)                               |
| n) Water solubility                             | No data available   |
| o) Partition coefficient: n-octanol/water       | log Pow: ca.0.25  |
| p) Auto-ignition                                | No data available   |



temperature

- |                              |                   |
|------------------------------|-------------------|
| q) Decomposition temperature | No data available |
| r) Viscosity                 | No data available |
| s) Explosive properties      | No data available |
| t) Oxidizing properties      | No data available |

## 9.2 Other safety information

No data available

---

## 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

No data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Heat, flames and sparks.

### 10.5 Incompatible materials

No data available

### 10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Nitrogen oxides (NOx)

Other decomposition products - No data available

In the event of fire: see section 5

---

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

#### Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

No data available

#### Skin corrosion/irritation

No data available

#### Serious eye damage/eye irritation

No data available

#### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

#### Carcinogenicity

No data available

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Acrylonitrile-2-13C)

NTP: RAHC - Reasonably anticipated to be a human carcinogen (Acrylonitrile-2-13C)

OSHA: OSHA specifically regulated carcinogen (Acrylonitrile-2-13C)

#### Reproductive toxicity

No data available



**Specific target organ toxicity - single exposure**

No data available

**Specific target organ toxicity - repeated exposure**

No data available

**Aspiration hazard**

No data available

**Additional Information**

RTECS: Not available

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated., May be partially metabolized to cyanide in the body., Central nervous system depression, Ataxia., Symptoms may be delayed.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

---

**12. ECOLOGICAL INFORMATION****12.1 Toxicity**

No data available

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available(Acrylonitrile-2-13C)

**12.5 Results of PBT and vPvB assessment**

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

**12.6 Other adverse effects**

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

---

**13. DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods****Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

**Contaminated packaging**

Dispose of as unused product.

---

**14. TRANSPORT INFORMATION****DOT (US)**

UN number: 1093      Class: 3 (6.1)      Packing group: I  
Proper shipping name: Acrylonitrile, stabilized  
Reportable Quantity (RQ) : 100 lbs

Poison Inhalation Hazard: No

ALL INNER PACKAGINGS MUST BE IN METAL CANS FOR FXG

**IMDG**

UN number: 1093 Class: 3 (6.1)

Packing group: I

EMS-No: F-E, S-D

Proper shipping name: ACRYLONITRILE, STABILIZED

Marine pollutant : yes

**IATA**

UN number: 1093 Class: 3 (6.1)

Packing group: I

Proper shipping name: Acrylonitrile, stabilized

IATA Passenger: Not permitted for transport

ALL INNER PACKAGINGS MUST BE PACKED WITH ABSORBANT MATERIAL IN TIGHTLY CLOSED METAL OR RIGID PLASTIC RECEPTACLES, ALL INNER PACKAGINGS MUST BE IN METAL CANS FOR FX AIR

---

## 15. REGULATORY INFORMATION

### SARA 302 Components

The following components are subject to reporting levels established by SARA Title III, Section 302:

|                     | CAS-No.    | Revision Date |
|---------------------|------------|---------------|
| Acrylonitrile-2-13C | 89511-33-1 | 2008-11-03    |

### SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

|                     | CAS-No.    | Revision Date |
|---------------------|------------|---------------|
| Acrylonitrile-2-13C | 89511-33-1 | 2008-11-03    |

### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

### Massachusetts Right To Know Components

|                     | CAS-No.    | Revision Date |
|---------------------|------------|---------------|
| Acrylonitrile-2-13C | 89511-33-1 | 2008-11-03    |

### Pennsylvania Right To Know Components

|                     | CAS-No.    | Revision Date |
|---------------------|------------|---------------|
| Acrylonitrile-2-13C | 89511-33-1 | 2008-11-03    |

### New Jersey Right To Know Components

|                     | CAS-No.    | Revision Date |
|---------------------|------------|---------------|
| Acrylonitrile-2-13C | 89511-33-1 | 2008-11-03    |

### California Prop. 65 Components

WARNING! This product contains a chemical known to the State of California to cause cancer.

|                     | CAS-No.    | Revision Date |
|---------------------|------------|---------------|
| Acrylonitrile-2-13C | 89511-33-1 | 2007-09-28    |

---

## 16. OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3.

|                    |   |
|--------------------|---|
| H225               | Highly flammable liquid and vapour.                     |
| H301               | Toxic if swallowed.                                     |
| H301 + H311 + H331 | Toxic if swallowed, in contact with skin or if inhaled. |
| H311               | Toxic in contact with skin.                             |
| H315               | Causes skin irritation.                                 |
| H317               | May cause an allergic skin reaction.                    |
| H318               | Causes serious eye damage.                              |
| H331               | Toxic if inhaled.                                       |
| H335               | May cause respiratory irritation.                       |

|      |  |
|------|--|
| H350 | May cause cancer.                                    |
| H361 | Suspected of damaging fertility or the unborn child. |
| H401 | Toxic to aquatic life.                               |
| H411 | Toxic to aquatic life with long lasting effects.     |

**Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

**Preparation Information**

Sigma-Aldrich Corporation  
Product Safety – Americas Region  
1-800-521-8956  
Version: 6.1

Revision Date: 07/25/2018

Print Date: 10/17/2019