

Printing date 07/31/2016

Reviewed on 07/31/2016

1 Identification

- **Product name**
- **Trade name:** Diethylaluminum chloride, 97%
- **Item number:** 93-1356
- **CAS Number:**
96-10-6
- **EC number:**
202-477-2
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Strem Chemicals, Inc.
7 Mulliken Way
NEWBURYPORT, MA 01950
USA
info@strem.com
- **Information department:** Technical Department
- **Emergency telephone number:**
EMERGENCY: CHEMTREC: + 1 (800) 424-9300
During normal opening times: +1 (978) 499-1600

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 1 H224 Extremely flammable liquid and vapor.

Self-heat. 2 H252 Self-heating in large quantities; may catch fire.

Water-react. 1 H260 In contact with water releases flammable gases, which may ignite spontaneously.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

- **Label elements**

- **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS05



GHS07

- **Signal word** *Danger*

(Contd. on page 2)

Safety Data Sheet according to OSHA HCS

Printing date 07/31/2016

Reviewed on 07/31/2016

Trade name: Diethylaluminum chloride, 97%

(Contd. of page 1)

• **Hazard-determining components of labeling:**

diethylaluminium chloride

• **Hazard statements**

H224 Extremely flammable liquid and vapor.

H252 Self-heating in large quantities; may catch fire.

H260 In contact with water releases flammable gases, which may ignite spontaneously.

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

• **Precautionary statements**

P231+P232 Handle under inert gas. Protect from moisture.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P422 Store contents under inert gas.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Classification system:**

• **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 4

Reactivity = 2

The substance demonstrates unusual reactivity with water.

• **HMIS-ratings (scale 0 - 4)**

HEALTH	4
FIRE	4
REACTIVITY	2

Health = 4

Fire = 4

Reactivity = 2

• **Other hazards**

• **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition/information on ingredients

• **Chemical characterization: Substances**

• **CAS No. Description**

96-10-6 diethylaluminium chloride

• **Identification number(s)**

• **EC number:** 202-477-2

4 First-aid measures

• **Description of first aid measures**

• **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

Safety Data Sheet according to OSHA HCS

Printing date 07/31/2016

Reviewed on 07/31/2016

Trade name: Diethylaluminum chloride, 97%

(Contd. of page 2)

- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Sand. Do not use water.
CO2, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

(Contd. on page 4)

Safety Data Sheet according to OSHA HCS

Printing date 07/31/2016

Reviewed on 07/31/2016

Trade name: Diethylaluminum chloride, 97%

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Keep receptacle tightly sealed.
 - Do not gas tight seal receptacle.
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

• **Components with limit values that require monitoring at the workplace:**

96-10-6 diethylaluminium chloride

REL Long-term value: 2 mg/m³
as Al

TLV Long-term value: 1* mg/m³
as Al;*as respirable fraction

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - Store protective clothing separately.
 - Avoid contact with the eyes.
 - Avoid contact with the eyes and skin.
- **Breathing equipment:**
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety Data Sheet
according to OSHA HCS

Printing date 07/31/2016

Reviewed on 07/31/2016

Trade name: Diethylaluminum chloride, 97%

(Contd. of page 4)

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Colorless
Odor:	Pungent
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	-85 °C (-121 °F)
Boiling point/Boiling range:	no data °C

· **Flash point:** -18 °C (-0 °F)

· **Flammability (solid, gaseous):** Not determined.

· **Ignition temperature:**

Decomposition temperature: Not determined.

· **Auto igniting:** Not determined.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

· **Vapor pressure at 80 °C (176 °F):** no data hPa

· **Density at 20 °C (68 °F):** 0.961 g/cm³ (8.02 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

· **Solvent content:**

Organic solvents:	0.0 %
VOC content:	0.0 g/l / 0.00 lb/gl

(Contd. on page 6)

Safety Data Sheet according to OSHA HCS

Printing date 07/31/2016

Reviewed on 07/31/2016

Trade name: Diethylaluminum chloride, 97%

(Contd. of page 5)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Contact with water releases flammable gases.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

96-10-6 diethylaluminium chloride

Oral LD50 11000 mg/kg (rat)

· **Primary irritant effect:**

· **on the skin:** Strong caustic effect on skin and mucous membranes.

· **on the eye:**

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

Substance is not listed.

· **NTP (National Toxicology Program)**

Substance is not listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

Substance is not listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:** Must not reach bodies of water or drainage ditch undiluted or unneutralized.

(Contd. on page 7)

Safety Data Sheet according to OSHA HCS

Printing date 07/31/2016

Reviewed on 07/31/2016

Trade name: Diethylaluminum chloride, 97%

(Contd. of page 6)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| • UN-Number | UN3394 |
| • DOT, IMDG, IATA | |
| • UN proper shipping name | Organometallic substance, liquid, pyrophoric, water-reactive (diethylaluminium chloride) |
| • DOT | ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER- REACTIVE (diethylaluminium chloride) |
| • IMDG | Organometallic substance, liquid, pyrophoric, water-reactive |
| • IATA | |
| • Transport hazard class(es) | |
| • DOT | |
|  | |
| • Class | 4.2 Substances liable to spontaneous combustion |
| • Label | 4.2, 4.3 |
| • IMDG | |
|  | |
| • Class | 4.2 Substances liable to spontaneous combustion |
| • Label | 4.2/4.3 |
| • IATA | |
|  | |
| • Class | 4.2 Substances liable to spontaneous combustion |
| • Label | 4.2 (4.3) |

(Contd. on page 8)

Safety Data Sheet according to OSHA HCS

Printing date 07/31/2016

Reviewed on 07/31/2016

Trade name: Diethylaluminum chloride, 97%

(Contd. of page 7)

· Packing group · DOT, IMDG, IATA	I
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category · Handling Code · Segregation Code	Not applicable. X333 F-G,S-M D H1 Keep as dry as reasonably practicable SG26 In addition: from goods of classes 2.1 and 3 when stowed on deck of a containership a minimum distance of two container spaces athwartship shall be maintained, when stowed on ro-ro ships a distance of 6 m athwartship shall be maintained. SG35 Stow "separated from" acids. SG63 Stow "separated longitudinally by an intervening complete compartment or hold from" Class 1.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information: · DOT · Quantity limitations	On passenger aircraft/rail: Forbidden On cargo aircraft only: Forbidden
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	0 Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 3394 ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE (DIETHYLALUMINIUM CHLORIDE), 4.2 (4.3), I

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

Substance is not listed.

· Section 313 (Specific toxic chemical listings):

Substance is not listed.

· TSCA (Toxic Substances Control Act):

Substance is listed.

· Proposition 65

· Chemicals known to cause cancer:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

(Contd. on page 9)

Safety Data Sheet according to OSHA HCS

Printing date 07/31/2016

Reviewed on 07/31/2016

Trade name: Diethylaluminum chloride, 97%

(Contd. of page 8)

• **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

• **Chemicals known to cause developmental toxicity:**

Substance is not listed.

• **Carcinogenic categories**

• **EPA (Environmental Protection Agency)**

Substance is not listed.

• **TLV (Threshold Limit Value established by ACGIH)**

Substance is not listed.

• **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

• **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

• **Hazard pictograms**



GHS02 GHS05 GHS07

• **Signal word** *Danger*

• **Hazard-determining components of labeling:**

diethylaluminium chloride

• **Hazard statements**

H224 Extremely flammable liquid and vapor.

H252 Self-heating in large quantities; may catch fire.

H260 In contact with water releases flammable gases, which may ignite spontaneously.

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

• **Precautionary statements**

P231+P232 Handle under inert gas. Protect from moisture.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P422 Store contents under inert gas.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Technical Department.

• **Contact:** Technical Director

• **Date of preparation / last revision** 07/31/2016 / -

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)

Safety Data Sheet according to OSHA HCS

Printing date 07/31/2016

Reviewed on 07/31/2016

Trade name: Diethylaluminum chloride, 97%

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Flam. Liq. 1: Flammable liquids, Hazard Category 1
 Self-heat. 2: Self-Heating Substances and Mixtures, Hazard Category 2
 Water-react. 1: Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 1
 Acute Tox. 4: Acute toxicity, Hazard Category 4
 Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A
 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

US