

1 Identification**Product identifier****Product name:** Beryllium carbide**Stock number:** 42136**CAS Number:**

506-66-1

Index number:

004-002-00-2

Relevant identified uses of the substance or mixture and uses advised against.**Identified use:** SU24 Scientific research and development**Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Alfa Aesar

Thermo Fisher Scientific Chemicals, Inc.

30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660

Fax: 800-322-4757

Email: tech@alfa.com

www.alfa.com

Information Department: Health, Safety and Environmental Department**Emergency telephone number:**

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

2 Hazard(s) identification**Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)**

GHS06 Skull and crossbones

Acute Tox. 3 H301 Toxic if swallowed.

Acute Tox. 2 H330 Fatal if inhaled.



GHS08 Health hazard

Carc. 1B H350 May cause cancer.

STOT RE 1 H372 Causes damage to the lung and the blood through prolonged or repeated exposure. Route of exposure: Inhalative.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Hazards not otherwise classified No information known.**Label elements****GHS label elements** The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)**Hazard pictograms**

GHS06 GHS08

Signal word Danger**Hazard statements**

H301 Toxic if swallowed.

H330 Fatal if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H335 May cause respiratory irritation.

H372 Causes damage to the lung and the blood through prolonged or repeated exposure. Route of exposure: Inhalative.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P320 Specific treatment is urgent (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

D1A - Very toxic material causing immediate and serious toxic effects

D2A - Very toxic material causing other toxic effects

**Classification system****HMIS ratings (scale 0-4)****(Hazardous Materials Identification System)**

HEALTH 3 Health (acute effects) = 3

FIRE 0 Flammability = 0

REACTIVITY 0 Physical Hazard = 0

Product name: **Beryllium carbide**

(Contd. of page 1)

Other hazards
Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Substances
CAS# Description:
506-66-1 Beryllium carbide
Identification number(s):
Index number: 004-002-00-2

4 First-aid measures

Description of first aid measures
General information
Immediately remove any clothing soiled by the product.
Remove breathing apparatus only after contaminated clothing has been completely removed.
In case of irregular breathing or respiratory arrest provide artificial respiration.
After inhalation
Supply fresh air. If required, provide artificial respiration. Keep patient warm.
Seek immediate medical advice.
After skin contact
Immediately wash with water and soap and rinse thoroughly.
Seek immediate medical advice.
After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing Do not induce vomiting; immediately call for medical help.
Information for doctor
Most important symptoms and effects, both acute and delayed No further relevant information available.
Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media
Suitable extinguishing agents Extinguishing powder. Do not use water.
For safety reasons unsuitable extinguishing agents Carbon dioxide
Special hazards arising from the substance or mixture
If this product is involved in a fire, the following can be released:
Toxic metal oxide fume
Carbon monoxide and carbon dioxide
Methane
Advice for firefighters
Protective equipment:
Wear self-contained respirator.
Wear fully protective impervious suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Environmental precautions: Do not allow material to be released to the environment without proper governmental permits.
Methods and material for containment and cleaning up:
Dispose of contaminated material as waste according to section 13.
Ensure adequate ventilation.
Prevention of secondary hazards: No special measures required.
Reference to other sections
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

Handling
Precautions for safe handling
Keep container tightly sealed.
Store in cool, dry place in tightly closed containers.
Ensure good ventilation at the workplace.
Open and handle container with care.
Information about protection against explosions and fires: Protect from humidity and water.
Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility: No information known.
Further information about storage conditions:
Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems:
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters
Components with limit values that require monitoring at the workplace:

Beryllium and compounds, as Be
mg/m³
ACGIH TLV 0.00005; 0.0002-STEL (inhalable fraction); Confirmed human carcinogen
Austria Carcinogen
Belgium TWA 0.002; Carcinogen
Denmark TWA 0.001
Finland TWA 0.002; 0.006-STEL; Carcinogen
France VME 0.002; C2 Carcinogen

(Contd. on page 3)
USA

Product name: Beryllium carbide

(Contd. of page 2)

Germany Carcinogen
Hungary TWA 0.001; Carcinogen
Japan OEL 0.002; 2A Carcinogen
Korea TLV 0.002; 0.01-STEL; Confirmed human carcinogen
Netherlands MAC-TGG 0.002; Carcinogen
Norway TWA 0.001
Poland TWA 0.001; 0.003-STEL
Russia 0.001-STEL; Carcinogen
Sweden NGV 0.002; Carcinogen
Switzerland MAK-W 0.002; Carcinogen
United Kingdom TWA 0.002; Carcinogen
USA PEL 0.002

Additional information: No data

Exposure controls

Personal protective equipment

General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Maintain an ergonomically appropriate working environment.

Breathing equipment: Use self-contained respiratory protective device in emergency situations.

Protection of hands:

Impervious gloves

Check protective gloves prior to each use for their proper condition.

The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Eye protection: Safety glasses

Body protection: Protective work clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form: Powder
Color: Yellow
Odor: Odorless
Odor threshold: Not determined.

pH-value: Not applicable.

Change in condition

Melting point/Melting range: >2100 °C (>3812 °F) ((dec) 0b/ b)
Boiling point/Boiling range: Not determined
Sublimation temperature / start: Not determined

Flash point: Not applicable
Flammability (solid, gaseous): Not determined.
Ignition temperature: Not determined
Decomposition temperature: Not determined
Auto igniting: Not determined.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined
Upper: Not determined
Vapor pressure: Not applicable.
Density at 20 °C (68 °F): 1.9 g/cm³ (15.856 lbs/gal)
Relative density: Not determined.
Vapor density: Not applicable.
Evaporation rate: Not applicable.
Solubility in / Miscibility with
Water: Not determined
Partition coefficient (n-octanol/water): Not determined.
Viscosity:
dynamic: Not applicable.
kinematic: Not applicable.
Other information No further relevant information available.

10 Stability and reactivity

Reactivity No information known.

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions No dangerous reactions known

Conditions to avoid No further relevant information available.

Incompatible materials: No information known.

Hazardous decomposition products:

Methane
Toxic metal oxide fume
Carbon monoxide and carbon dioxide

11 Toxicological information

Information on toxicological effects

Acute toxicity:

Fatal if inhaled.
Toxic if swallowed.

LD/LC50 values that are relevant for classification: No data

Skin irritation or corrosion: Causes skin irritation.

Eye irritation or corrosion: Causes serious eye irritation.

Sensitization: May cause an allergic skin reaction.

Germ cell mutagenicity: No effects known.

(Contd. on page 4)
USA

Product name: Beryllium carbide

(Contd. of page 3)

Carcinogenicity:

May cause cancer.
EPA-B2: Probable human carcinogen, sufficient evidence from animal studies; inadequate evidence or no data from epidemiologic studies.
IARC-1: Carcinogenic to humans: sufficient evidence of carcinogenicity.
NTP-R: Reasonably anticipated to be a carcinogen: limited evidence from studies in humans or sufficient evidence from studies in experimental animals.
ACGIH A1: Confirmed human carcinogen: Agent is carcinogenic to humans based on epidemiologic studies of, or convincing clinical evidence in, exposed humans.

Reproductive toxicity: No effects known.

Specific target organ system toxicity - repeated exposure:

Causes damage to the lung and the blood through prolonged or repeated exposure. Route of exposure: Inhalative.

Specific target organ system toxicity - single exposure: May cause respiratory irritation.

Aspiration hazard: No effects known.

Subacute to chronic toxicity:

Acute exposure to beryllium may cause dermatitis, chronic skin ulcers, rhinitis, nasopharyngitis, epistaxis, bronchitis, pneumonitis possibly fatal, fever, rales, dyspnea and substernal pain. Chronic exposure causes a delayed form of lung disease which may be delayed for five years or more after exposure stops. Symptoms include coughing, shortness of breath, loss of appetite, weight loss and fatigue. Cyanosis is common with elevated pulse and respiratory rates. This disease may progress to death from cardiac or respiratory failure.

Subacute to chronic toxicity: No effects known.

Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for aquatic organisms

Additional ecological information:

General notes:

Do not allow material to be released to the environment without proper governmental permits.
Toxic for aquatic organisms
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic to aquatic life.
May cause long lasting harmful effects to aquatic life.
Avoid transfer into the environment.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation Consult state, local or national regulations to ensure proper disposal.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number
DOT, IMDG, IATA

UN1566

UN proper shipping name
DOT
IMDG, IATA

Beryllium compounds, n.o.s. (Beryllium carbide)
BERYLLIUM COMPOUND, N.O.S. (Beryllium carbide)

Transport hazard class(es)

DOT



Class 6.1 Toxic substances.
Label 6.1
Class 6.1 (T5) Toxic substances
Label 6.1
IMDG, IATA 6.1



Class 6.1 Toxic substances.
Label 6.1

Packing group
DOT, IMDG, IATA

II

Environmental hazards:

Environmentally hazardous substance, solid

Special precautions for user

Warning: Toxic substances

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

DOT
Marine Pollutant (DOT): No
Item:

UN "Model Regulation": UN1566, Beryllium compounds, n.o.s. (Beryllium carbide), 6.1, II

Product name: **Beryllium carbide**

(Contd. of page 4)

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)
Hazard pictograms



GHS06 GHS08

Signal word Danger

Hazard statements

H301 Toxic if swallowed.

H330 Fatal if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H335 May cause respiratory irritation.

H372 Causes damage to the lung and the blood through prolonged or repeated exposure. Route of exposure: Inhalative.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P320 Specific treatment is urgent (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

SARA Section 313 (specific toxic chemical listings)

506-66-1 Beryllium carbide

California Proposition 65

Prop 65 - Chemicals known to cause cancer

506-66-1 Beryllium carbide

Prop 65 - Developmental toxicity Substance is not listed.

Prop 65 - Developmental toxicity, female Substance is not listed.

Prop 65 - Developmental toxicity, male Substance is not listed.

Information about limitation of use:

For use only by technically qualified individuals.

This product contains beryllium and is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act of 1986 and 40CFR372.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Global Marketing Department

Date of preparation / last revision 11/23/2015 / -

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

vPvB: very Persistent and very Bioaccumulative

ACGIH: American Conference of Governmental Industrial Hygienists (USA)

OSHA: Occupational Safety and Health Administration (USA)

NTP: National Toxicology Program (USA)

IARC: International Agency for Research on Cancer

EPA: Environmental Protection Agency (USA)